


FIXTURE WEIGHT 12 LBS




FIXTURE WEIGHT 18 LBS



AP1-S1SA-18-GW-BAL



FIXTURE WEIGHT 13 LBS



FIXTURE WEIGHT 20 LBS



AP1-S1SB-18-GW-GRP

MATCHING FIXTURES







page 176



page 444

FEATURES

- The Apollo is an updated version of a 1920s Art Deco light fixture.
- Light gently spills between the two stacked, low profile trim rings and radiates on the wall surface.
- Spun from solid, non-ferrous 0.040" thick brass, 0.040" thick copper or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 AP1	S1SA INDOOR ADA COMPLIANT SCNCE 	18	GW GLOSS WHITE ACRYLIC	PAL POLISHED ALUMINUM	18" 	120	DMA ADVANCE® DIMMING BALLAST
			MW MATTE WHITE ACRYLIC	BAL BRUSHED ALUMINUM			2QD13 2@13W QD (13793.0)
		27	FA FAUX ALABASTER ACRYLIC	PTR PEWTER	2IN40 2@40W IN (13808.0)	347	EMR REMOTE MOUNT EMERGENCY
			NH NATURAL HORN ACRYLIC	PBR POLISHED BRASS			27" 
			ET ETRUSCAN ACRYLIC	BBR BRUSHED BRASS	2BX27 2@27W BX		ULD UL DAMP LABEL
			WS WHITE SWIRL ACRYLIC	ABR ANTIQUE BRASS			2IN40 2@40W IN
		18	GW GLOSS WHITE ACRYLIC	PAL POLISHED ALUMINUM	18"	120	DMA ADVANCE® DIMMING BALLAST
			MW MATTE WHITE ACRYLIC	BAL BRUSHED ALUMINUM			2QD13 2@13W QD (13809.0)
		27	FA FAUX ALABASTER ACRYLIC	PTR PEWTER	2IN100 2@100W IN (13792.0)	347	EMR REMOTE MOUNT EMERGENCY
			NH NATURAL HORN ACRYLIC	PBR POLISHED BRASS			27"
			ET ETRUSCAN ACRYLIC	BBR BRUSHED BRASS	2QD26 2@26W QD (12201.0)		ULD UL DAMP LABEL
			WS WHITE SWIRL ACRYLIC	ABR ANTIQUE BRASS			2IN100 2@100W IN (13792.0)
			PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	STB STATUARY BRONZE			
				SNK SATIN NICKEL			
				ORB OIL RUBBED BRONZE			
				PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)			

▾ SPECIFY CATALOG CODE

SAMPLE CODE: **AP1-S1SB-18-GW-GRP-2QD13-120-FUS**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- ADA compliant version available.
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.