



AL1-C1NA-16-GW-BNP



AL1-C1NA-16-GW-BAL

MATCHING FIXTURES



page 52



page 58



page 342



page 488

FEATURES

- The low-profile trim ring of the Ariel was originally designed for the University of Toledo bookstore.
- A transitional design makes it a welcome piece for both contemporary and traditional applications.
- Spun from solid, non-ferrous 0.040" thick brass or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS	
 <p>AL1</p>	<p>C1NA SURFACE CEILING MOUNT</p> 	16	GW GLOSS WHITE ACRYLIC	PAL POLISHED ALUMINUM	16"	120	DMA ADVANCE® DIMMING BALLAST	
			MW MATTE WHITE ACRYLIC	BAL BRUSHED ALUMINUM			2QD13 2@13W QD (13789.0)	277 DML LUTRON® DIMMING BALLAST
		26	PTA PEWTER	PTR PEWTER	26"	347	2IN60 2@60W IN	EMR REMOTE MOUNT EMERGENCY
			FA FAUX ALABASTER ACRYLIC	PBR POLISHED BRASS			2QD26 2@26W QD (13812.0)	FUS FUSED
			NH NATURAL HORN ACRYLIC	BBR BRUSHED BRASS	4QD26 4@26W QD (12205.0)	2IN100 2@100W IN	ULD UL DAMP LABEL	
			ET ETRUSCAN ACRYLIC	ABR ANTIQUE BRASS				
			WS WHITE SWIRL ACRYLIC	STB STATUARY BRONZE				
				SNK SATIN NICKEL				
			ORB OIL RUBBED BRONZE					
			PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)					

▾ SPECIFY CATALOG CODE

SAMPLE CODE: **AL1-C1NA-16-GW-BAL-2QD13-120-ULD**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others) and may require additional anchors on larger sizes.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.