

AV1-S1SC-19-GW-BKP

▾ MATCHING FIXTURES



page 120



page 124



page 330





page 462



page 482

▾ FEATURES

- The shallow acrylic diffuser of the Avalon arm sconce sits atop a sturdy arm assembly, creating an exciting play of light, both against the wall surface and into the surrounding space.
- The simple, understated look of this fixture is well suited for numerous interior applications.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 <p>AV1</p>	<p>S1SC ARM SCNCE</p> 	19	<p>GW GLOSS WHITE ACRYLIC</p>	<p>PAL POLISHED ALUMINUM</p>	<p>19"</p>	120	<p>DMA ADVANCE® DIMMING BALLAST</p>
			<p>MW MATTE WHITE ACRYLIC</p>	<p>BAL BRUSHED ALUMINUM</p>	<p>20D26 2@26W QD</p>	277	<p>DML LUTRON® DIMMING BALLAST</p>
		23	<p>FA FAUX ALABASTER ACRYLIC</p>	<p>PTR PEWTER</p>	<p>3IN60 3@60W IN</p>	347	<p>EMI INTEGRAL EMERGENCY</p>
			<p>FB FAUX BRASS ACRYLIC</p>	<p>PBR POLISHED BRASS</p>	<p>23"</p>		<p>FUS FUSED</p>
			<p>NH NATURAL HORN ACRYLIC</p>	<p>BBR BRUSHED BRASS</p>	<p>4QD26 4@26W QD (10989.0)</p>		<p>ULD UL DAMP LABEL</p>
			<p>ET ETRUSCAN ACRYLIC</p>	<p>ABR ANTIQUE BRASS</p>	<p>4TT32 4@32W TT (9529.0)</p>		<p>TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)</p>
			<p>WS WHITE SWIRL ACRYLIC</p>	<p>STB STATUARY BRONZE</p>	<p>3IN150 3@150W IN (13742.0)</p>		
				<p>SNK SATIN NICKEL</p>			
				<p>ORB OIL RUBBED BRONZE</p>			
				<p>PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>			

☐ SPECIFY CATALOG CODE

SAMPLE CODE: AV1-S1SC-19-GW-BKP-2QD26-120-FUS

☐ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.
- ADA compliant version available.
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.