


FIXTURE WEIGHT 8 LBS



FIXTURE WEIGHT 14 LBS



FIXTURE WEIGHT 18 LBS



AV1-C1NA-16-GW-SMP

▼ MATCHING FIXTURES



page 120



page 124



page 330





page 332



page 482

▼ FEATURES

- The Avalon features a simple, shallow dome and is accented by a small bottom finial.
- Its transitional design makes it a welcome piece for both contemporary and traditional applications.
- Constructed with solid, non-ferrous brass or aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 AV1	C1NA SURFACE CEILING MOUNT 	16	GW GLOSS WHITE ACRYLIC	PAL POLISHED ALUMINUM BAL BRUSHED ALUMINUM	16" 2QD13 2@13W QD (13789.0)	120 277	DMA ADVANCE® DIMMING BALLAST DML LUTRON® DIMMING BALLAST
		19	MW MATTE WHITE ACRYLIC	PTR PEWTER PBR POLISHED BRASS	19" 2QD26 2@26W QD (12190.0)	347 FUS FUSED	EMR REMOTE MOUNT EMERGENCY
		23	FA FAUX ALABASTER ACRYLIC	BBR BRUSHED BRASS ABR ANTIQUE BRASS	23" 2QD26 2@26W QD (13812.0)	ULD UL DAMP LABEL	
			NH NATURAL HORN ACRYLIC	STB STATUARY BRONZE SNK SATIN NICKEL	4QD26 4@26W QD (12205.0)		
			ET ETRUSCAN ACRYLIC	ORB OIL RUBBED BRONZE PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)			
			WS WHITE SWIRL ACRYLIC				

☐ SPECIFY CATALOG CODE

SAMPLE CODE: AV1-C1NA-16-GW-SMP-2QD13-120-FUS

☒ PHOTOMETRIC INFORMATION
 AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others) and may require additional anchors on larger sizes.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.