



AVALON™ PENDANT



AV1-P4AB-23-GW-BMP

MATCHING FIXTURES



page 120



page 330



page 332







page 462



page 482

FEATURES

- The simple, shallow dome of the Avalon is accented by vertical hanging systems.
- Constructed with solid, non-ferrous brass or aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS
 <p>AV1</p>	<p>P2AB DOUBLE CLUSTER PENDANT WITH A SINGLE CENTER STEM AND A LARGER DIAMETER NON-TAPERED BOTTOM SECTION</p> 	23	<p>GW GLOSS WHITE ACRYLIC</p> <p>MW MATTE WHITE ACRYLIC</p>	<p>PAL POLISHED ALUMINUM</p> <p>BAL BRUSHED ALUMINUM</p> <p>PTR PEWTER</p>	<p>23"</p> <p>4QD26 4@26W QD [10989.0]</p> <p>4TT32 4@32W TT [9529.0]</p>	120	48	<p>DMA ADVANCE® DIMMING BALLAST</p> <p>DML LUTRON® DIMMING BALLAST</p>
	<p>P3AB TRIPLE CLUSTER PENDANT WITH A SINGLE CENTER STEM AND A LARGER DIAMETER NON-TAPERED BOTTOM SECTION</p> 	30	<p>FA FAUX ALABASTER ACRYLIC</p> <p>NH NATURAL HORN ACRYLIC</p> <p>ET ETRUSCAN ACRYLIC</p> <p>WS WHITE SWIRL ACRYLIC</p>	<p>PBR POLISHED BRASS</p> <p>BBR BRUSHED BRASS</p> <p>ABR ANTIQUE BRASS</p> <p>STB STATUARY BRONZE</p> <p>SNK SATIN NICKEL</p> <p>ORB OIL RUBBED BRONZE</p> <p>PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>	<p>3IN150 3@150W IN [13742.0]</p> <p>30"</p> <p>8QD26 8@26W QD [12189.0]</p> <p>4BX39 4@39W BX [9640.0]</p> <p>6BX39 6@39W BX [8668.0]</p> <p>6IN150 6@150W IN [13743.0]</p>	277	347	<p>EMI INTEGRAL EMERGENCY</p> <p>FUS FUSED</p> <p>ULD UL DAMP LABEL</p>
	<p>P4AB QUAD CLUSTER PENDANT WITH A SINGLE CENTER STEM AND A LARGER DIAMETER NON-TAPERED BOTTOM SECTION</p> 			<p>NOTE: ON ALL BRASS AND PLATED FINISHES, CLUSTER ARMS WILL BE POWDER COAT PAINTED.</p>	<p>NOTE: LAMPING LISTED IS PER BOWL.</p>			
<p>↓ SPECIFY CATALOG CODE</p>								

SAMPLE CODE: AV1-P4AB-23-GW-BMP-4QD26-120-48-FUS

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture requires structural mounting.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- If sloped-ceiling adapter is required, consult factory for details.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.