



## AVALON™ PEDESTAL



AV1-L1PC-19-GW-BAL

### MATCHING FIXTURES



page 120



page 124



page 330





page 332



page 462

### FEATURES

- The simple, shallow dome of the Avalon is accented by a vertical hanging system.
- Constructed with solid, non-ferrous brass or aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS
 AV1	L1PC PEDESTAL WITH 4 VERTICAL STEMS 	19	<b>GW</b> GLOSS WHITE ACRYLIC	<b>PAL</b> POLISHED ALUMINUM	<b>19"</b> <b>2QD26</b> 2@26W QD (13771.0)	<b>120</b> <b>277</b>	<b>24</b>	<b>DMA</b> ADVANCE® DIMMING BALLAST
			<b>MW</b> MATTE WHITE ACRYLIC	<b>BAL</b> BRUSHED ALUMINUM				<b>2IN100</b> 2@100W IN (7135.0)
		23	<b>FA</b> FAUX ALABASTER ACRYLIC	<b>PBR</b> POLISHED BRASS	<b>23"</b> <b>4QD26</b> 4@26W QD (10989.0) <b>4TT32</b> 4@32W TT (9529.0) <b>3IN150</b> 3@150W IN (13742.0)	<b>30</b>	<b>EMI</b> INTEGRAL EMERGENCY	
			<b>NH</b> NATURAL HORN ACRYLIC	<b>BBR</b> BRUSHED BRASS			<b>FUS</b> FUSED	
			<b>NH</b> NATURAL HORN ACRYLIC	<b>ABR</b> ANTIQUE BRASS			<b>TLP</b> TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)	
			<b>ET</b> ETRUSCAN ACRYLIC	<b>STB</b> STATUARY BRONZE			<b>ULD</b> UL DAMP LABEL	
			<b>ET</b> ETRUSCAN ACRYLIC	<b>SNK</b> SATIN NICKEL				
			<b>WS</b> WHITE SWIRL ACRYLIC	<b>ORB</b> OIL RUBBED BRONZE				
				<b>PTD</b> PAINTED - SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)				
		<div style="display: flex; justify-content: space-between;"> <span>↓ SPECIFY CATALOG CODE</span> <span>↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM</span> </div>						

SAMPLE CODE: AV1-L1PC-19-GW-BAL-2QD26-120-24-TLP

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.
- Maximum overall height is 49" from the top of the fixture to the mounting surface.
- For photometric data, please visit [www.ocl.com](http://www.ocl.com).
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.