



FIXTURE WEIGHT 4 LBS




FIXTURE WEIGHT 6 LBS



AV1-S1SA-13-GW-NFA



FIXTURE WEIGHT 5 LBS



FIXTURE WEIGHT 7 LBS



AV1-S1SB-13-GW-PBR

MATCHING FIXTURES



page 120



page 124



page 332









page 462



page 482

FEATURES

- The simple dome of the Avalon emits a soft glow.
- Its minimal design makes it a welcome piece for both contemporary and traditional applications.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 AV1	<b>S1SA</b> INDOOR ADA COMPLIANT SCONCE 	13	<b>GW</b> GLOSS WHITE ACRYLIC  <b>MW</b> MATTE WHITE ACRYLIC	<b>NFA</b> NO FINISH AVAILABLE	<b>13"</b>  <b>10D26</b> 1@26W QD (13781.0) <b>2IN40</b> 2@40W IN	<b>120</b>  <b>277</b>  <b>347</b>	<b>DMA</b> ADVANCE® DIMMING BALLAST <b>DML</b> LUTRON® DIMMING BALLAST <b>EMR</b> REMOTE MOUNT EMERGENCY <b>FUS</b> FUSED <b>ULD</b> UL DAMP LABEL <b>TLP</b> TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)
		16	<b>FA</b> FAUX ALABASTER ACRYLIC  <b>NH</b> NATURAL HORN ACRYLIC  <b>ET</b> ETRUSCAN ACRYLIC  <b>WS</b> WHITE SWIRL ACRYLIC		<b>16"</b>  <b>20D26</b> 2@26W QD <b>2IN40</b> 2@40W IN (13808.0)		
 AV1	<b>S1SB</b> INDOOR SCONCE 	13	<b>GW</b> GLOSS WHITE ACRYLIC  <b>MW</b> MATTE WHITE ACRYLIC	<b>PAL</b> POLISHED ALUMINUM  <b>BAL</b> BRUSHED ALUMINUM  <b>PTR</b> PEWTER  <b>PBR</b> POLISHED BRASS  <b>BBR</b> BRUSHED BRASS  <b>ABR</b> ANTIQUE BRASS  <b>STB</b> STATUARY BRONZE  <b>SNK</b> SATIN NICKEL  <b>ORB</b> OIL RUBBED BRONZE  PTD PAINTED - SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	<b>13"</b> <b>20D13</b> 2@13W QD (13782.0) <b>2IN40</b> 2@40W IN	<b>120</b>  <b>277</b>  <b>347</b>	<b>DMA</b> ADVANCE® DIMMING BALLAST <b>DML</b> LUTRON® DIMMING BALLAST <b>EMR</b> REMOTE MOUNT EMERGENCY <b>FUS</b> FUSED <b>ULD</b> UL DAMP LABEL <b>TLP</b> TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)
		16	<b>FA</b> FAUX ALABASTER ACRYLIC  <b>NH</b> NATURAL HORN ACRYLIC  <b>ET</b> ETRUSCAN ACRYLIC  <b>WS</b> WHITE SWIRL ACRYLIC		<b>16"</b> <b>20D26</b> 2@26W QD <b>2IN60</b> 2@60W IN (12201.0)		

☑ SPECIFY CATALOG CODE

SAMPLE CODE: **AV1-S1SB-13-GW-PBR-20D13-120-FUS**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT [WWW.OCL.COM](http://WWW.OCL.COM)

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- ADA compliant version available.
- For photometric data, please visit [www.ocl.com](http://www.ocl.com).
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.