




CAIRO™ PENDANT



FIXTURE WEIGHT 20 LBS



FIXTURE WEIGHT 35 LBS



FIXTURE WEIGHT 50 LBS



CR1-P1EG-25-GW-GRP



MATCHING FIXTURES



page 366

FEATURES

- The Cairo pendant is inspired by the great pyramids in Egypt and is fabricated from 0.080" thick aluminum.
- Custom panel designs are available. Consult factory for details.
- 1/8" thick virgin white acrylic window panels are UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS		
 CR1	P1EG PENDANT WITH 4 ANGLED AIRCRAFT CABLES TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY 	25	GW GLOSS WHITE ACRYLIC MW MATTE WHITE ACRYLIC	PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	25" 40D26 4@26W QD 4TT32 4@32W TT (13776.0) 4BX39 4@39W BX 3IN150 3@150W IN	120 277 347	34	DMA ADVANCE® DIMMING BALLAST DML LUTRON® DIMMING BALLAST EMI INTEGRAL EMERGENCY FUS FUSED		
					35" 8TT32 8@32W TT (13777.0) 6BX39 6@39W BX 6BX40 6@40W BX 6BX50 6@50W BX 6BX55 6@55W BX 6IN150 6@150W IN	43			TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT) ULD UL DAMP LABEL TRC TRIPLE CIRCUIT	
					45" 8TT42 8@42W TT 9BX39 9@39W BX 9BX40 9@40W BX 9BX50 9@50W BX 9BX55 9@55W BX 8IN150 8@150W IN	50				
		<input type="button" value="SPECIFY CATALOG CODE"/>								

SAMPLE CODE: CR1-P1EG-25-GW-GRP-4TT32-120-30-FUS

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others), and features a 45-degree sloped-ceiling canopy.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.

- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.

PENDANT