



CAIRO™ SCNCE



FIXTURE WEIGHT 6 LBS



FIXTURE WEIGHT 9 LBS



CR1-S1SA-18-GW-GRP

ADA




MATCHING FIXTURES



page 224

FEATURES

- The Cairo sconce was inspired by the great pyramids in Egypt and is fabricated from 0.080" thick aluminum.
- Consult with factory for modified face designs or acrylic colors.
- 1/8" thick, virgin white acrylic window panels are UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 CR1	S1SA INDOOR ADA COMPLIANT SCONCE 	18	GW GLOSS WHITE ACRYLIC	BAL BRUSHED ALUMINUM PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	18"  2QD26 2@26W QD 1BX27 1@27W BX (13790.0)	120 277 347	DMA ADVANCE® DIMMING BALLAST DML LUTRON® DIMMING BALLAST EMR REMOTE MOUNT EMERGENCY FUS FUSED ULD UL DAMP LABEL TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)
			MW MATTE WHITE ACRYLIC				
 CR1	S1SB INDOOR SCONCE 	26	GW GLOSS WHITE ACRYLIC	BAL BRUSHED ALUMINUM PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	26" 2QD26 2@26W QD 2TT32 2@32W TT 2TT42 2@42W TT 2BX39 2@39W BX 2BX40 2@40W BX 1BX50 1@50W BX (13795.0) 2BX50 2@50W BX 2BX55 2@55W BX	120 277 347	DMA ADVANCE® DIMMING BALLAST DML LUTRON® DIMMING BALLAST EMR REMOTE MOUNT EMERGENCY FUS FUSED ULD UL DAMP LABEL TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)
			MW MATTE WHITE ACRYLIC				

☑ SPECIFY CATALOG CODE

SAMPLE CODE: **CR1-S1SA-18-GW-GRP-2QD26-120-ULD**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- ADA compliant version available.
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.