



CL1-S1SA-18-FA-ABR

ADA



CL1-S1SA-14-GW-PTR



▾ MATCHING FIXTURES



page 154



page 158



page 298












page 434



page 470

▾ FEATURES

- A single, cast brass shell accents the trim ring of the Calypso and is the focal point of this 1920s reproduction.
- The classic look of crown molding creates a stately appearance.
- Spun from solid, non-ferrous 0.040" thick brass, 0.040" thick copper, or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.




SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 <p>CL1</p>	S1SA INDOOR ADA COMPLIANT SCNCE 	15	GW GLOSS WHITE ACRYLIC	PAL POLISHED ALUMINUM	15" 	120	DMA ADVANCE® DIMMING BALLAST
			MW MATTE WHITE ACRYLIC	BAL BRUSHED ALUMINUM	2QD13 2@13W QD (13793.0)	277	DML LUTRON® DIMMING BALLAST
		18	FA FAUX ALABASTER ACRYLIC	PTR PEWTER	2IN40 2@40W IN (13808.0)	347	EMR REMOTE MOUNT EMERGENCY
			NH NATURAL HORN ACRYLIC	PBR POLISHED BRASS	18" 	FUS FUSED	
		24	ET ETRUSCAN ACRYLIC	BBR BRUSHED BRASS	2QD13 2@13W QD (13793.0)	ULD UL DAMP LABEL	
			WS WHITE SWIRL ACRYLIC	ABR ANTIQUE BRASS	2IN40 2@40W IN (13808.0)	TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)	
		PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	STB STATUARY BRONZE	24" 	2BX27 2@27W BX		
ORB OIL RUBBED BRONZE	SNK SATIN NICKEL	2IN40 2@40W IN					
 <p>CL1</p>	S1SA INDOOR ADA COMPLIANT SCNCE 	14	GW GLOSS WHITE ACRYLIC	PAL POLISHED ALUMINUM	14" 	120	DMA ADVANCE® DIMMING BALLAST
			MW MATTE WHITE ACRYLIC	BAL BRUSHED ALUMINUM	1QD26 1@26W QD (13781.0)	277	DML LUTRON® DIMMING BALLAST
		20	FA FAUX ALABASTER ACRYLIC	PTR PEWTER	2IN40 2@40W IN	347	EMR REMOTE MOUNT EMERGENCY
			NH NATURAL HORN ACRYLIC	PBR POLISHED BRASS	20" 	FUS FUSED	
			ET ETRUSCAN ACRYLIC	BBR BRUSHED BRASS	2QD26 2@26W QD	ULD UL DAMP LABEL	
			WS WHITE SWIRL ACRYLIC	ABR ANTIQUE BRASS	2IN40 2@40W IN (13808.0)	TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)	
		PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	STB STATUARY BRONZE	SNK SATIN NICKEL			
ORB OIL RUBBED BRONZE	SNK SATIN NICKEL	ORB OIL RUBBED BRONZE					

☑ SPECIFY CATALOG CODE

SAMPLE CODE: **CL1-S1SA-14-GW-PTR-1QD26-120-TLP**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- ADA compliant version available.
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.



CL1-S1SB-18-FA-ORB



CL1-S1SB-18-GW-PBR

▾ MATCHING FIXTURES



page 154



page 158



page 296





page 434



page 470

▾ FEATURES

- A single, cast brass shell accents the trim ring of the Calypso and is the focal point of this 1920s reproduction.
- The classic look of crown molding creates a stately appearance.
- Spun from solid, non-ferrous 0.040" thick brass, 0.040" thick copper, or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 CL1	S1SB INDOOR SCONCE 	15	GW GLOSS WHITE ACRYLIC	PAL POLISHED ALUMINUM	15" 2QD13 2@13W QD (13809.0)	120 277	DMA ADVANCE® DIMMING BALLAST
			MW MATTE WHITE ACRYLIC	BAL BRUSHED ALUMINUM			DML LUTRON® DIMMING BALLAST
		18	FA FAUX ALABASTER ACRYLIC	PTR PEWTER	18" 2IN40 2@40W IN	347	EMR REMOTE MOUNT EMERGENCY (15" SIZE ONLY)
			NH NATURAL HORN ACRYLIC	PBR POLISHED BRASS			EMI INTEGRAL EMERGENCY (18"/24" SIZES ONLY)
		24	ET ETRUSCAN ACRYLIC	BBR BRUSHED BRASS	2QD26 2@26W QD (12201.0)	2IN100 2@100W IN (13792.0)	FUS FUSED
			WS WHITE SWIRL ACRYLIC	ABR ANTIQUE BRASS			ULD UL DAMP LABEL
			STB STATUARY BRONZE	24" 2TT32 2@32W TT (13807.0)	TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)		
			SNK SATIN NICKEL		2IN100 2@100W IN (13792.0)	VOL "V" STYLE OVERLAY AND BOTTOM FINIAL	
			ORB OIL RUBBED BRONZE	PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)		OOL "O" STYLE OVERLAY AND BOTTOM FINIAL	

☑ SPECIFY CATALOG CODE

SAMPLE CODE: CL1-S1SB-18-GW-PBR-2QD26-120-TLP

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- ADA compliant version available.
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.