




CAMELOT™ PENDANT



FIXTURE WEIGHT 30 LBS



FIXTURE WEIGHT 45 LBS




FIXTURE WEIGHT 80 LBS




CM2-P16D-25-FA-PBR




CM2-P1AJ-25-GW-STB



FIXTURE WEIGHT 30 LBS



FIXTURE WEIGHT 45 LBS



FIXTURE WEIGHT 80 LBS

MATCHING FIXTURES



page 206



page 208



page 304



page 428

FEATURES

- The Camelot is a re-creation of a historical classic.
- Cast from solid, non-ferrous brass or aluminum, the trim ring features the classic Egg-and-Dart architectural detail.
- The optional v-style overlay and acorn style cast brass bottom finial add another level of elegance.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS
<p>CM1 (SHALLOW DIFFUSER)</p> <p>CM2 (DEEP DIFFUSER)</p>	P1AF PENDANT WITH 4 REEDED VERTICAL STEMS TO CANOPY AND A SINGLE REEDED CENTER STEM FROM TRIM RING TO CANOPY	17	GW GLOSS WHITE ACRYLIC MW MATTE WHITE ACRYLIC	PTR PEWTER PBR POLISHED BRASS BBR BRUSHED BRASS	17" 20D26 2@26W QD (13771.0) 2IN100 2@100W IN (7135.0)	120 277 347	24 32	DMA ADVANCE® DIMMING BALLAST DML LUTRON® DIMMING BALLAST
		25	FA FAUX ALABASTER ACRYLIC NH NATURAL HORN ACRYLIC	ABR ANTIQUE BRASS STB STATUARY BRONZE	25" 40D26 4@26W QD (10989.0)	32	EMI INTEGRAL EMERGENCY FUS FUSED	
	P1AJ PENDANT WITH 3 ANGLED REEDED STEMS TO CANOPY AND A SINGLE REEDED CENTER STEM FROM TRIM RING TO CANOPY (17"/25" SIZES ONLY)	32	ET ETRUSCAN ACRYLIC WS WHITE SWIRL ACRYLIC	SNK SATIN NICKEL ORB OIL RUBBED BRONZE PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	32" 80D26 8@26W QD (12189.0) 4BX40 4@40W BX 4BX50 4@50W BX (8480.0) 4BX55 4@55W BX 8BX39 8@39W BX (12187.0) 3IN150 3@150W IN (7130.0)	54	TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT) CIB CLEAR INNER BOWL ULD UL DAMP LABEL TRC TRIPLE CIRCUIT BFL BOTTOM FINIAL (SEE BELOW) VOL "V" STYLE OVERLAY AND BOTTOM FINIAL OOL "O" STYLE OVERLAY AND BOTTOM FINIAL	
			P1AK PENDANT WITH 3 ANGLED REEDED STEMS AND A CENTER REEDED STEM TO COLLECTOR AND A SINGLE CENTER CHAIN FROM COLLECTOR TO CANOPY (32" SIZE ONLY)	P16D PENDANT WITH 3 ANGLED CHAINS TO CANOPY AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY (17"/25" SIZES ONLY)	P16F PENDANT WITH 3 ANGLED CHAINS AND A CENTER REEDED STEM TO COLLECTOR AND A SINGLE CENTER CHAIN FROM COLLECTOR TO CANOPY (32" SIZE ONLY)			

↓ SPECIFY CATALOG CODE

SAMPLE CODE: **CM2-P1AJ-25-GW-STB-4TT32-120-38-TLP**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM


- Fixture mounts to a standard 4" J-box (supplied by others), and features a 7-degree ceiling canopy (standard on all hanging systems except "P1AF").
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.

- Bottom finial option increases overall height by length of the finial.
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For metal halide lamping contact factory.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.




BFL
BOTTOM FINIAL


CAMELOT™ PENDANT



FIXTURE WEIGHT 30 LBS



FIXTURE WEIGHT 45 LBS




FIXTURE WEIGHT 80 LBS




CM1-P1AF-25-MW-ABR-VOL




CM1-P1AJ-25-GW-BKP



FIXTURE WEIGHT 30 LBS



FIXTURE WEIGHT 45 LBS



FIXTURE WEIGHT 80 LBS

MATCHING FIXTURES



page 202



page 208



page 304



page 428

FEATURES

- The Camelot is a re-creation of a historical classic.
- Cast from solid, non-ferrous brass or aluminum, the trim ring features the classic Egg-and-Dart architectural detail.
- The optional v-style overlay and acorn style cast brass bottom finial add another level of elegance.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS			
 	P1AF PENDANT WITH 4 REEDED VERTICAL STEMS TO CANOPY AND A SINGLE REEDED CENTER STEM FROM TRIM RING TO CANOPY 	17	GW GLOSS WHITE ACRYLIC	PTR PEWTER	17"	120	22	DMA ADVANCE® DIMMING BALLAST			
			MW MATTE WHITE ACRYLIC	PBR POLISHED BRASS				20D26 2@26W QD (13771.0)	277	DML LUTRON® DIMMING BALLAST	
		25	FA FAUX ALABASTER ACRYLIC	ABR ANTIQUE BRASS	25"	347	29	EMI INTEGRAL EMERGENCY			
			NH NATURAL HORN ACRYLIC	STB STATUARY BRONZE				40D26 4@26W QD (10989.0)	FUS FUSED		
		32	P1AJ PENDANT WITH 3 ANGLED REEDED STEMS TO CANOPY AND A SINGLE REEDED CENTER STEM FROM TRIM RING TO CANOPY (17"/25" SIZES ONLY) 	ET ETRUSCAN ACRYLIC	SNK SATIN NICKEL	32"	50	TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)			
				WS WHITE SWIRL ACRYLIC	ORB OIL RUBBED BRONZE			3IN100 3@100W IN (7130.1)	ULD UL DAMP LABEL		
	P1AK PENDANT WITH 3 ANGLED REEDED STEMS AND A CENTER REEDED STEM TO COLLECTOR AND A SINGLE CENTER CHAIN FROM COLLECTOR TO CANOPY (32" SIZE ONLY) 	P1GD PENDANT WITH 3 ANGLED CHAINS TO CANOPY AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY (17"/25" SIZES ONLY) 	PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS) 80D26 8@26W QD (12189.0) 4BX40 4@40W BX 4BX50 4@50W BX (8480.0) 4BX55 4@55W BX 8BX39 8@39W BX (12187.0) 3IN150 3@150W IN (7130.0)	TRC TRIPLE CIRCUIT							
				P16F PENDANT WITH 3 ANGLED CHAINS AND A CENTER REEDED STEM TO COLLECTOR AND A SINGLE CENTER CHAIN FROM COLLECTOR TO CANOPY (32" SIZE ONLY) 	BFL BOTTOM FINIAL (SEE BELOW)						
		VOL "V" STYLE OVERLAY AND BOTTOM FINIAL									
		OOL "O" STYLE OVERLAY AND BOTTOM FINIAL									
		<input type="checkbox"/> SPECIFY CATALOG CODE									

SAMPLE CODE: **CM1-P1AJ-25-GW-BKP-4TT32-120-38-TLP**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others), and features a 7-degree ceiling canopy (standard on all hanging systems except "P1AF").
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.

- Bottom finial option increases overall height by length of the finial.
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For metal halide lamping contact factory.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.



BFL
BOTTOM FINIAL