







CAMELOT SIGNATURE™ PENDANT



CS1-P1AK-54-GW-STB



CS2-P1AK-54-FA-PBR



MATCHING FIXTURES



page 202



page 206






page 304



page 428

FEATURES

- Cast brass arms and the Camelot cast trim ring are combined to make this signature fixture.
- Cast from solid, non-ferrous brass or aluminum, the trim ring features the classic Egg-and-Dart architectural detail.
- The optional v-style overlay and acorn style cast brass bottom finial add another level of elegance.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS	
 CS1* (SATELLITE DIFFUSERS FROSTED WHITE GLASS GLOBES)	P1AK PENDANT WITH 3 ANGLED REEDED STEMS AND A CENTER REEDED STEM TO COLLECTOR AND A SINGLE CENTER CHAIN FROM COLLECTOR TO CANOPY 	34	GW GLOSS WHITE ACRYLIC	PTR PEWTER	34"	120	42	DMA ADVANCE® DIMMING BALLAST	
			MW MATTE WHITE ACRYLIC	PBR POLISHED BRASS	20D26 2@26W QD	277		DML LUTRON® DIMMING BALLAST	
 CS2 (SATELLITE DIFFUSERS ACRYLIC DOMES)		42	FA FAUX ALABASTER ACRYLIC	ABR ANTIQUE BRASS	42"	347	50	EMI INTEGRAL EMERGENCY	
			NH NATURAL HORN ACRYLIC	STB STATUARY BRONZE	40D26 4@26W QD			FUS FUSED	
		54	ET ETRUSCAN ACRYLIC	SNK SATIN NICKEL	4TT32 4@32W TT		54	TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)	
			WS WHITE SWIRL ACRYLIC	ORB OIL RUBBED BRONZE	3IN100 3@100W IN			ULD UL DAMP LABEL	
				PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	80D26 8@26W QD			TRC TRIPLE CIRCUIT	
					4BX40 4@40W BX			BFL BOTTOM FINIAL (SEE BELOW)	
					4BX50 4@50W BX			VOL "V" STYLE OVERLAY AND BOTTOM FINIAL	
					4BX55 4@55W BX			00L "O" STYLE OVERLAY AND BOTTOM FINIAL	
					8BX39 8@39W BX				
					3IN150 3@150W IN				
*NOTE: ROUND GLOBES ONLY AVAILABLE IN FROSTED WHITE GLASS.					NOTE: SATELLITE DIFFUSERS ILLUMINATED BY 60W A-LAMPS ONLY				
<input type="button" value="SPECIFY CATALOG CODE"/>									

SAMPLE CODE: CS2-P1AK-54-FA-PBR-4TT32-120-54-TLP

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture requires structural mounting.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.

- Bottom finial option increases overall height by length of the finial.
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For metal halide lamping contact factory.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.



BFL
BOTTOM FINIAL