


FIXTURE WEIGHT 4 LBS



C01-S1SA-12-GW-GRP

ADA



FIXTURE WEIGHT 5 LBS










C02-S1SA-18-GW-GRP

ADA



**FEATURES**

- The Core features a solid, aluminum die-cast center hub.
- 0.20" thick, injection molded diffuser fully encircles the lamps.
- Virgin white acrylic is UV stable and UL-94 HB Flame Class rated.
- Simply unscrew diffusers to re-lamp.
- Core can be mounted vertically or horizontally.
- One or two lamp versions available.
- 21 standard powder coat paints offered, however all RAL colors available.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 <p>CO1</p>	<p>S1SA INDOOR ADA COMPLIANT SCNCE</p> 	12	<p>GW GLOSS WHITE ACRYLIC</p>	<p>PTD PAINTED – SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>	<p>12" </p> <p>10D13 1@13W QD (13803.0)</p>	<p>120 277 347</p>	<p>EMR REMOTE MOUNT EMERGENCY</p> <p>ULD UL DAMP LABEL</p>
 <p>CO2</p>	<p>S1SA INDOOR ADA COMPLIANT SCNCE</p> 	18	<p>GW GLOSS WHITE ACRYLIC</p>	<p>PTD PAINTED – SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>	<p>18" </p> <p>20D13 2@13W QD (13802.0)</p>	<p>120 277 347</p>	<p>EMR REMOTE MOUNT EMERGENCY</p> <p>ULD UL DAMP LABEL</p>
<p> SPECIFY CATALOG CODE</p>							

SCNCE

SAMPLE CODE: C02-S1SA-18-GW-GRP-2QD13-120

 PHOTOMETRIC INFORMATION AVAILABLE AT [WWW.OCL.COM](http://WWW.OCL.COM)

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Fixture is ADA compliant.
- For photometric data, please visit [www.ocl.com](http://www.ocl.com).
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.