


DC1-P1AA-10-WG-SMP



UN1-P1AA-10-WG-STB

▼ MATCHING FIXTURES



page 360



page 360






page 422



page 422

▼ FEATURES

- The Deco and Urn series feature unique styles of hand-blown opal white glass.
- This timeless fixture is available with energy efficient compact fluorescent lamping.
- Constructed with solid, non-ferrous brass, aluminum or copper.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent, metal halide and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS
 DC1   UN1	<b>P1AA</b> PENDANT WITH A SINGLE CENTER STEM 	10	WG WHITE GLASS	<b>PAL</b> POLISHED ALUMINUM <b>BAL</b> BRUSHED ALUMINUM <b>PTR</b> PEWTER <b>PBR</b> POLISHED BRASS <b>BBR</b> BRUSHED BRASS <b>ABR</b> ANTIQUE BRASS <b>STB</b> STATUARY BRONZE <b>SNK</b> SATIN NICKEL <b>ORB</b> OIL RUBBED BRONZE  <b>PTD</b> PAINTED - SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	<b>10"</b> <b>4QD26</b> 4@26W QD [9685.0] <b>2TT32</b> 2@32W TT <b>1TT42</b> 1@42W TT [13764.0] <b>1IN150</b> 1@150W IN [13763.0] <b>1MH100</b> 1@100W MH	<b>120</b> <b>277</b> <b>347</b>	<b>42</b>	<b>DMA</b> ADVANCE® DIMMING BALLAST <b>DML</b> LUTRON® DIMMING BALLAST <b>EMI</b> INTEGRAL EMERGENCY <b>FUS</b> FUSED <b>ULD</b> UL DAMP LABEL <b>MHC</b> 24" METAL HALIDE BALLAST CANOPY (100W & LOWER ONLY)
								SPECIFY CATALOG CODE

SAMPLE CODE: UN1-P1AA-10-WG-STB-2TT32-120-34-FUS

PHOTOMETRIC INFORMATION AVAILABLE AT [WWW.OCL.COM](http://WWW.OCL.COM)

- Fixture mounts to a standard 4" J-box (supplied by others), and features a 45-degree sloped-ceiling canopy.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Maximum overall height subject to ballast specification. Consult factory for details.

- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.
- Remote mounted F-can ballast standard for metal halide lamping (20' max for 100w). Metal halide ballast canopy available for 100w only.
- For photometric data, please visit [www.ocl.com](http://www.ocl.com).
- For lamp and base information, see pages 496-505 in the reference section.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.



DECO CANOPY FOR INCANDESCENT LAMPING

URN CANOPY FOR INCANDESCENT LAMPING