




FIXTURE WEIGHT 4 LBS



FIXTURE WEIGHT 5 LBS



FIXTURE WEIGHT 6 LBS



FIXTURE WEIGHT 7 LBS



EL1-S1SA-24-GW-AWP

ADA



EL1-S1SA-24-GW-AWP

ADA

▾ MATCHING FIXTURES









page 380



page 454

▾ FEATURES

- The Element features an extruded aluminum back channel 2.50" wide and 0.125" thick with a matte anodized protective coating.
- Features solid aluminum die-cast ends.
- 3/16" thick extruded virgin white acrylic is 45% DR high impact, UV stable, F1 rated, and UL-94 HB Flame Class rated.
- Element can be mounted vertically or horizontally.
- Tamper-proof stainless steel screws available as an option.
- 21 standard powder coat paints offered, however all RAL colors available.
- Utilizes highly efficient, long lasting and low mercury T5 or T5HO lamps for minimal fixture maintenance and lamp disposal.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 EL1	S1SA INDOOR ADA COMPLIANT SCNCE 	24	GW GLOSS WHITE ACRYLIC MW MATTE WHITE ACRYLIC	PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	24"  1LF14 1@14W T5 1LF24 1@24W T5H0 (13767.0)	120 277 347	DMA ADVANCE® DIMMING BALLAST DML LUTRON® DIMMING BALLAST EMR REMOTE MOUNT EMERGENCY (24"/36" SIZES ONLY) EMI INTEGRAL EMERGENCY (48"/60" SIZES ONLY) ULD UL DAMP LABEL FUS FUSED SJB MOUNTING COVER FOR STANDARD 4" J-BOX (SEE BELOW) TPS TAMPER PROOF SCREWS
		36	36"  1LF21 1@21W T5		1LF39 1@39W T5H0 (13768.0)		
		48	48"  1LF28 1@28W T5		1LF54 1@54W T5H0 (13769.0)		
		60	60"  1LF35 1@35W T5		1LF80 1@80W T5H0 (13770.0)		
		SPECIFY CATALOG CODE					

SAMPLE CODE: **EL1-S1SA-24-GW-AWP-1LF14-120-FUS**

 PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 2" x 4" switch box (supplied by others), and requires additional anchors. See options section for standard 4" J-box mounting.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).

- Fixture is ADA compliant.
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.



SJB
MOUNTING COVER FOR STANDARD 4" J-BOX