





EA1-P1AH-27-WS-ORB



EA1-P1AA-27-GW-BAL

MATCHING FIXTURES



page 164



page 302






page 436



page 472

FEATURES

- The simple and elegant trim ring of the Ella makes it perfectly suited for both contemporary and traditional applications.
- Spun from solid, non-ferrous 0.040" thick brass or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS
 EA1	<b>P1AA</b> PENDANT WITH A SINGLE CENTER STEM 	17	<b>GW</b> GLOSS WHITE ACRYLIC	<b>PAL</b> POLISHED ALUMINUM	<b>17"</b>	<b>120</b>	24	<b>DMA</b> ADVANCE® DIMMING BALLAST
			<b>MW</b> MATTE WHITE ACRYLIC	<b>BAL</b> BRUSHED ALUMINUM	<b>4QD26</b> 4@26W QD (10989.0)	<b>277</b>		<b>DML</b> LUTRON® DIMMING BALLAST
		27	<b>FA</b> FAUX ALABASTER ACRYLIC	<b>PBR</b> POLISHED BRASS	<b>27"</b>	<b>347</b>	32	<b>EMI</b> INTEGRAL EMERGENCY
			<b>NH</b> NATURAL HORN ACRYLIC	<b>BBR</b> BRUSHED BRASS	<b>4TT32</b> 4@32W TT (9529.0)	<b>FUS</b> FUSED		
		34	<b>P1AH</b> PENDANT WITH 3 ANGLED STEMS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY 	<b>ET</b> ETRUSCAN ACRYLIC	<b>ABR</b> ANTIQUE BRASS	<b>4TT42</b> 4@42W TT	40	<b>TLP</b> TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)
				<b>WS</b> WHITE SWIRL ACRYLIC	<b>STB</b> STATUARY BRONZE	<b>4BX39</b> 4@39W BX (8222.1)		
	PTD PAINTED - SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)			<b>SNK</b> SATIN NICKEL	<b>3IN150</b> 3@150W IN (13742.0)			
	<b>ORB</b> OIL RUBBED BRONZE			<b>34"</b>	<b>80D26</b> 8@26W QD (12189.0)			
	42					<b>6BX40</b> 6@40W BX <b>6BX50</b> 6@50W BX (9531.0) <b>6BX55</b> 6@55W BX <b>8BX39</b> 8@39W BX (12187.0)	50	<b>CIB</b> CLEAR INNER BOWL
								<b>ULD</b> UL DAMP LABEL
								<b>TRC</b> TRIPLE CIRCUIT
								<b>DNL</b> PAR DOWN LIGHT
<b>BFL</b> BOTTOM FINIAL (SEE BELOW)								
<b>VOL</b> "V" STYLE OVERLAY AND BOTTOM FINIAL								
<b>00L</b> "O" STYLE OVERLAY AND BOTTOM FINIAL								


↓ SPECIFY CATALOG CODE

SAMPLE CODE: EA1-P1AA-27-GW-BAL-4TT32-120-30-TLP

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others), and features a 45-degree sloped-ceiling canopy.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.
- Bottom finial option increases overall height by length of the finial.

- For photometric data, please visit [www.ocl.com](http://www.ocl.com).
- For lamp and base information, see pages 496-505 in the reference section.
- Par down light option available in combination with a variety of compact fluorescent reflectors.
- For metal halide lamping contact factory.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.



**BFL**  
BOTTOM FINIAL