



ES1-C1NA-17-GW-BMP

▾ MATCHING FIXTURES



page 172



page 308



page 308

▾ FEATURES

- The Essex trim features triangular perforations which emit a subtle glow.
- Custom laser-cut perforations are available. Consult factory for details.
- Spun from solid, non-ferrous 0.040" thick brass or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 ES1	C1NA SURFACE CEILING MOUNT 	17	GW GLOSS WHITE ACRYLIC	PAL POLISHED ALUMINUM	17" 2QD13 2@13W QD (13789.0) 2QD26 2@26W QD (12190.0) 2IN60 2@60W IN	120 277 347	DMA ADVANCE® DIMMING BALLAST
			MW MATTE WHITE ACRYLIC	BAL BRUSHED ALUMINUM			DML LUTRON® DIMMING BALLAST
			FA FAUX ALABASTER ACRYLIC	PTR PEWTER			EMR REMOTE MOUNT EMERGENCY (17" SIZE ONLY)
			27	PBR POLISHED BRASS			EMI INTEGRAL EMERGENCY (27" SIZE ONLY)
			NH NATURAL HORN ACRYLIC	BBR BRUSHED BRASS			FUS FUSED
		ET ETRUSCAN ACRYLIC	ABR ANTIQUE BRASS	2QD26 2@26W QD (13812.0)	ULD UL DAMP LABEL		
		WS WHITE SWIRL ACRYLIC	STB STATUARY BRONZE	4QD26 4@26W QD (12205.0)			
			SNK SATIN NICKEL	2IN100 2@100W IN			
			ORB OIL RUBBED BRONZE				
			PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)				

▾ SPECIFY CATALOG CODE

SAMPLE CODE: **ES1-C1NA-17-GW-BMP-2QD13-120-ULD**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others) and may require additional anchors on larger sizes.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.