


ES1-S1SA-11-FA-ABR

ADA



ES1-S1SB-17-GW-BAL

MATCHING FIXTURES









page 172



page 440

FEATURES

- The Essex trim features triangular perforations which emit a subtle glow.
- Custom laser-cut perforations are available. Consult factory for details.
- Spun from solid, non-ferrous 0.040" thick brass or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 ES1	S1SA INDOOR ADA COMPLIANT SCNCE 	11	GW GLOSS WHITE ACRYLIC MW MATTE WHITE ACRYLIC	PAL POLISHED ALUMINUM BAL BRUSHED ALUMINUM	11"  2QD13 2@13W QD	120 277	DMA ADVANCE® DIMMING BALLAST DML LUTRON® DIMMING BALLAST
		16	FA FAUX ALABASTER ACRYLIC NH NATURAL HORN ACRYLIC ET ETRUSCAN ACRYLIC WS WHITE SWIRL ACRYLIC	PTR PEWTER PBR POLISHED BRASS BBR BRUSHED BRASS ABR ANTIQUE BRASS STB STATUARY BRONZE SNK SATIN NICKEL ORB OIL RUBBED BRONZE PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	1QD26 1@26W QD (13785.0) 2IN40 2@40W IN 16"  2BX27 2@27W BX (12404.0) 2BX39 2@39W BX 2IN60 2@60W IN	347 EMI INTEGRAL EMERGENCY (16" SIZE ONLY) FUS FUSED ULD UL DAMP LABEL TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT) BLP BOTTOM LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)	
 ES1	S1SB INDOOR SCNCE 	17	GW GLOSS WHITE ACRYLIC MW MATTE WHITE ACRYLIC	PAL POLISHED ALUMINUM BAL BRUSHED ALUMINUM	17" 2QD26 2@26W QD (12201.0)	120 277	DMA ADVANCE® DIMMING BALLAST DML LUTRON® DIMMING BALLAST
		27	FA FAUX ALABASTER ACRYLIC NH NATURAL HORN ACRYLIC ET ETRUSCAN ACRYLIC WS WHITE SWIRL ACRYLIC	PTR PEWTER PBR POLISHED BRASS BBR BRUSHED BRASS ABR ANTIQUE BRASS STB STATUARY BRONZE SNK SATIN NICKEL ORB OIL RUBBED BRONZE PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	2IN100 2@100W IN (13792.0) 27" 2TT32 2@32W TT (13807.0) 2IN100 2@100W IN (13792.0)	347 EMR REMOTE MOUNT EMERGENCY (17" SIZE ONLY) EMI INTEGRAL EMERGENCY (27" SIZE ONLY) FUS FUSED ULD UL DAMP LABEL TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)	

☑ SPECIFY CATALOG CODE

SAMPLE CODE: **ES1-S1SB-17-GW-BAL-2QD26-120-ULD**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- ADA compliant version available.
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.