

FIXTURE WEIGHT & LBS



FX1-S1SA-18-MW-BAL

ADA





FX1-S1SA-18-MW-GRP

ADA



FEATURES

- The Flux sconce features a fully enclosed vacuum-formed acrylic diffuser and has a bulbous shape.
- The Flux features a formed sheet metal face from 0.064" thick aluminum.
- Flux can be mounted vertically or horizontally.
- Virgin white acrylic is UV stable and UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 <p>FX1</p>	<p>S1SA INDOOR ADA COMPLIANT SCONCE</p> 	<p>18</p>	<p>MW MATTE WHITE ACRYLIC</p>	<p>PAL POLISHED ALUMINUM BAL BRUSHED ALUMINUM PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>	<p>18"  20D26 2@26W QD (13800.0)</p>	<p>120 277 347</p>	<p>DMA ADVANCE® DIMMING BALLAST DML LUTRON® DIMMING BALLAST EMR REMOTE MOUNT EMERGENCY FUS FUSED ULD UL DAMP LABEL</p>
<p>↓ SPECIFY CATALOG CODE</p>							

SAMPLE CODE: **FX1-S1SA-18-MW-GRP-20D26-120-ULD**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Fixture is ADA compliant.
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.

SCONCE