




FUSE™ PENDANT




FIXTURE WEIGHT 30 LBS



FIXTURE WEIGHT 35 LBS



FIXTURE WEIGHT 40 LBS





FIXTURE WEIGHT 50 LBS



FU1-P1EG-24-GW-BAL

FEATURES

- The Fuse features 1/4" thick interlocking aluminum water jet-cut, decorative cross bars which are gracefully suspended by four stainless steel aircraft cables.
- Custom water jet-cut cross bars are available. Consult factory for details.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS
 FU1	P1EG PENDANT WITH 4 ANGLED AIRCRAFT CABLES TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY 	24	GW GLOSS WHITE ACRYLIC	PAL POLISHED ALUMINUM	24"	120	30	DMA ADVANCE® DIMMING BALLAST
			MW MATTE WHITE ACRYLIC	BAL BRUSHED ALUMINUM	4QD26 4@26W QD (10989.0)	277		DML LUTRON® DIMMING BALLAST
			FA FAUX ALABASTER ACRYLIC	PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	4TT32 4@32W TT (9529.0)	347		EMI INTEGRAL EMERGENCY
		32	NH NATURAL HORN ACRYLIC	38	8QD26 8@26W QD (12189.0)	36	FUS FUSED	
					4BX39 4@39W BX (9640.0)		TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)	
					6BX39 6@39W BX (8668.0)		ULD UL DAMP LABEL	
					6IN150 6@150W IN (13743.0)			TRC TRIPLE CIRCUIT
					38"			
					8TT32 8@32W TT (13746.0)			
		43	ET ETRUSCAN ACRYLIC	43	6BX40 6@40W BX	48		
					6BX50 6@50W BX (13745.0)			
					6BX55 6@55W BX			
					6IN150 6@150W IN (13743.0)			
					9BX39 9@39W BX			
					9BX40 9@40W BX			
		43	WS WHITE SWIRL ACRYLIC	43	9BX50 9@50W BX (13747.0)	48		
					9BX55 9@55W BX			
					8IN150 8@150W IN (13744.0)			

☑ SPECIFY CATALOG CODE

SAMPLE CODE: **FU1-P1EG-24-GW-BAL-4TT32-120-30-FUS**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others), and features a 45-degree sloped-ceiling canopy.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.

- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For metal halide lamping contact factory.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.