




## GATSBY™ PENDANT





GT1-P1AA-23-GW-PAL



### FEATURES

- White, thermally-formed diffuser with concentric ribs gives the Gatsby a unique, retro appearance.
- Small to medium sized pendant provides general direct and indirect illumination.
- Virgin white acrylic is UV stable and UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS
 <p>GT1</p>	<p>P1AA PENDANT WITH A SINGLE CENTER STEM</p> 	19	<b>GW</b> GLOSS WHITE ACRYLIC <b>MW</b> MATTE WHITE ACRYLIC	<b>PAL</b> POLISHED ALUMINUM <b>BAL</b> BRUSHED ALUMINUM <b>PTR</b> PEWTER <b>PBR</b> POLISHED BRASS <b>BBR</b> BRUSHED BRASS	<b>19"</b> <b>1TT26</b> 1@26W TT <b>1TT32</b> 1@32W TT <b>1TT42</b> 1@42W TT (13765.0)	<b>120</b> <b>277</b> <b>347</b>	<b>24</b>	<b>DMA</b> ADVANCE® DIMMING BALLAST REQUIRES 12" BALLAST CANOPY (SEE BELOW) <b>DML</b> LUTRON® DIMMING BALLAST REQUIRES 12" BALLAST CANOPY (SEE BELOW)
			23	<b>ABR</b> ANTIQUE BRASS <b>STB</b> STATUARY BRONZE <b>SNK</b> SATIN NICKEL <b>ORB</b> OIL RUBBED BRONZE	<b>23"</b> <b>1TT42</b> 1@42W TT (12328.0) <b>1TT57</b> 1@57W TT <b>1TT70</b> 1@70W TT	<b>30</b>	<b>EMI</b> INTEGRAL EMERGENCY REQUIRES 12" BALLAST CANOPY (SEE BELOW)	
				32	<b>PTD</b> PAINTED - SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	<b>32"</b> <b>1IN150</b> 1@150W IN <b>2TT32</b> 2@32W TT <b>2TT42</b> 2@42W TT (13766.0) <b>1TT57</b> 1@57W TT <b>1TT70</b> 1@70W TT <b>1IN200</b> 1@200W IN	<b>36</b>	<b>FUS</b> FUSED <b>ULD</b> UL DAMP LABEL


☑ SPECIFY CATALOG CODE

SAMPLE CODE: **GT1-P1AA-23-GW-PAL-1TT42-120-34-FUS**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT [WWW.OCL.COM](http://WWW.OCL.COM)

- Fixture mounts to a standard 4" J-box (supplied by others) and comes with a standard 45-degree sloped ceiling canopy.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).

- Maximum OAH subject to ballast specification. Consult factory for details.
- For photometric data, please visit [www.ocl.com](http://www.ocl.com).
- For lamp and base information, see pages 496-505 in the reference section.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.



**DMA/DML/EMI**  
REQUIRES 12" BALLAST CANOPY