

HL1-C1NA-21-GW-BAL

▾ MATCHING FIXTURES




page 186



page 310

▾ FEATURES

- A frosted acrylic disc floats above the trim ring to create the Halo series.
- Light transfuses through the acrylic to create a halo around the fixture.
- Spun from solid, non-ferrous 0.040" thick brass, 0.040" thick copper, or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

| SERIES | HANGING SYSTEM | SIZE | DIFFUSER | FINISH | LAMPING (PHOTOMETRIC TEST #) | VOLTAGE | OPTIONS | |
|--|--|------|---|-------------------------------------|------------------------------|-------------------|---|--|
|  <p>HL1</p> | <p>C1NA SURFACE CEILING MOUNT</p>  | 21 | <p>GW GLOSS WHITE ACRYLIC</p> | <p>PAL POLISHED ALUMINUM</p> | <p>21"</p> | <p>120</p> | <p>DMA ADVANCE® DIMMING BALLAST</p> <p>DML LUTRON® DIMMING BALLAST</p> <p>EMR REMOTE MOUNT EMERGENCY</p> <p>FUS FUSED</p> <p>ULD UL DAMP LABEL</p> | |
| | | | <p>MW MATTE WHITE ACRYLIC</p> | <p>BAL BRUSHED ALUMINUM</p> | | | | <p>2QD13 2@13W QD (13789.0)</p> |
| | | 32 | <p>FA FAUX ALABASTER ACRYLIC</p> | <p>PTR PEWTER</p> | <p>32"</p> | <p>347</p> | | |
| | | | <p>NH NATURAL HORN ACRYLIC</p> | <p>PBR POLISHED BRASS</p> | | | | <p>2IN60 2@60W IN</p> |
| | | | <p>ET ETRUSCAN ACRYLIC</p> | <p>BBR BRUSHED BRASS</p> | | | | <p>2QD26 2@26W QD (13812.0)</p> |
| | | | <p>WS WHITE SWIRL ACRYLIC</p> | <p>ABR ANTIQUE BRASS</p> | | | | <p>4QD26 4@26W QD (12205.0)</p> |
| | | | <p>PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p> | <p>STB STATUARY BRONZE</p> | | | | <p>2IN100 2@100W IN</p> |
| | | | <p>SNK SATIN NICKEL</p> | <p>ORB OIL RUBBED BRONZE</p> | | | | |

☐ SPECIFY CATALOG CODE

SAMPLE CODE: **HL1-C1NA-21-GW-BAL-2QD13-120-EMR**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others) and may require additional anchors on larger sizes.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.