


FIXTURE WEIGHT 8 LBS




FIXTURE WEIGHT 13 LBS



HL1-S1SA-21-GW-BKP/SMP



FIXTURE WEIGHT 9 LBS



FIXTURE WEIGHT 14 LBS



HL1-S1SB-21-GW-BAL

MATCHING FIXTURES








page 186



page 446

FEATURES

- A frosted acrylic disc floats above the trim ring to create the Halo series.
- Light transfuses through the acrylic to create a halo around the fixture.
- Spun from solid, non-ferrous 0.040" thick brass, 0.040" thick copper or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS			
 <p>HL1</p>	<p>S1SA INDOOR ADA COMPLIANT SCNCE</p> 	21	<p>GW GLOSS WHITE ACRYLIC</p>	<p>PAL POLISHED ALUMINUM</p>	<p>21" </p> <p>2QD13 2@13W QD (13793.0)</p> <p>2IN40 2@40W IN (13808.0)</p>	<p>120</p> <p>277</p> <p>347</p>	<p>DMA ADVANCE® DIMMING BALLAST</p> <p>DML LUTRON® DIMMING BALLAST</p> <p>EMR REMOTE MOUNT EMERGENCY</p> <p>FUS FUSED</p> <p>ULD UL DAMP LABEL</p> <p>TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)</p>			
			<p>MW MATTE WHITE ACRYLIC</p>	<p>BAL BRUSHED ALUMINUM</p>						
			32	<p>FA FAUX ALABASTER ACRYLIC</p>				<p>PTR PEWTER</p>		
				<p>NH NATURAL HORN ACRYLIC</p>				<p>PBR POLISHED BRASS</p>		
				<p>ET ETRUSCAN ACRYLIC</p>				<p>BBR BRUSHED BRASS</p>		
				<p>WS WHITE SWIRL ACRYLIC</p>				<p>ABR ANTIQUE BRASS</p>		
		<p>PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>		<p>STB STATUARY BRONZE</p>						
		<p>SNK SATIN NICKEL</p>		<p>ORB OIL RUBBED BRONZE</p>						
		 <p>HL1</p>	<p>S1SB INDOOR SCNCE</p> 	21	<p>GW GLOSS WHITE ACRYLIC</p>	<p>PAL POLISHED ALUMINUM</p>		<p>21"</p> <p>2QD13 2@13W QD (13809.0)</p> <p>2IN100 2@100W IN (13792.0)</p>	<p>120</p> <p>277</p> <p>347</p>	
					<p>MW MATTE WHITE ACRYLIC</p>	<p>BAL BRUSHED ALUMINUM</p>				
					32	<p>FA FAUX ALABASTER ACRYLIC</p>				<p>PTR PEWTER</p>
						<p>NH NATURAL HORN ACRYLIC</p>				<p>PBR POLISHED BRASS</p>
<p>ET ETRUSCAN ACRYLIC</p>	<p>BBR BRUSHED BRASS</p>									
<p>WS WHITE SWIRL ACRYLIC</p>	<p>ABR ANTIQUE BRASS</p>									
<p>PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>	<p>STB STATUARY BRONZE</p>									
<p>SNK SATIN NICKEL</p>	<p>ORB OIL RUBBED BRONZE</p>									

☑ SPECIFY CATALOG CODE

SAMPLE CODE: **HL1-S1SB-21-GW-BAL-2QD13-120-FUS**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- ADA compliant version available.
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.