




HOGARTH™ PENDANT



FIXTURE WEIGHT 22 LBS



FIXTURE WEIGHT 28 LBS




FIXTURE WEIGHT 38 LBS




HG1-P1GE-26-FA-ABR




HG1-P1AD-26-MW-BNP



FIXTURE WEIGHT 22 LBS



FIXTURE WEIGHT 28 LBS



FIXTURE WEIGHT 38 LBS




MATCHING FIXTURES



page 334

FEATURES

- The Hogarth features a decorative cone shaped ceiling canopy and gentle, curved acrylic diffuser.
- A solid turned brass bottom final accents the curvature of the diffuser.
- Constructed with solid, non-ferrous brass or aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS
 HG1	P1AD PENDANT WITH 3 VERTICAL SATELLITE STEMS AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY 	20	GW GLOSS WHITE ACRYLIC	PAL POLISHED ALUMINUM	20"	120	28	DMA ADVANCE® DIMMING BALLAST
			MW MATTE WHITE ACRYLIC	BAL BRUSHED ALUMINUM	4QD26 4@26W QD (10989.0)	277		DML LUTRON® DIMMING BALLAST
		26	FA FAUX ALABASTER ACRYLIC	PBR POLISHED BRASS	26"	347	34	EMI INTEGRAL EMERGENCY
			P1GE PENDANT WITH 3 ANGLED CHAINS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY 	BBR BRUSHED BRASS	4TT32 4@32W TT (9529.0)	FUS FUSED		
		37		NH NATURAL HORN ACRYLIC	ABR ANTIQUE BRASS	3IN150 3@150W IN (13742.0)	42	TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)
				ET ETRUSCAN ACRYLIC	STB STATUARY BRONZE	6TT42 6@42W TT		ULD UL DAMP LABEL
	WS WHITE SWIRL ACRYLIC			ORB OIL RUBBED BRONZE	8QD26 8@26W QD (12189.0)	TRC TRIPLE CIRCUIT		
	PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)			8TT32 8@32W TT (13746.0)	6IN150 6@150W IN (13743.0)	EQS 45-DEGREE SWIVEL SUITABLE FOR EARTHQUAKE CODES (SEE BELOW)		

↓ SPECIFY CATALOG CODE

SAMPLE CODE: **HG1-P1AD-26-MW-BNP-4TT32-120-36-FUS**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others), and features a 7-degree ceiling canopy.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.

- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For metal halide lamping contact factory.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.



EQS
45-DEGREE SWIVEL SUITABLE FOR EARTHQUAKE CODES