









HORIZON™ PENDANT



HR1-P1ED-26-GW-BAL



HR1-P1AE-26-GW-BAL

MATCHING FIXTURES



page 340








page 450



page 486

FEATURES

- The Horizon features a low-profile, minimalist square trim.
- A transitional design makes it a welcome addition to both contemporary and traditional applications.
- Spun from solid, non-ferrous 0.040" thick brass or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS
 <p>HR1</p>	<b>P1AA</b> PENDANT WITH A SINGLE CENTER STEM 	16	<b>GW</b> GLOSS WHITE ACRYLIC	<b>PAL</b> POLISHED ALUMINUM	<b>16"</b>	<b>120</b>	21	<b>DMA</b> ADVANCE® DIMMING BALLAST
			<b>MW</b> MATTE WHITE ACRYLIC	<b>BAL</b> BRUSHED ALUMINUM	<b>20D26</b> 2@26W QD (13771.0)	<b>277</b>		<b>DML</b> LUTRON® DIMMING BALLAST
	<b>P1AE</b> PENDANT WITH 4 VERTICAL STEMS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY 	26	<b>FA</b> FAUX ALABASTER ACRYLIC	<b>PBR</b> POLISHED BRASS	<b>26"</b>	<b>347</b>	32	<b>EMI</b> INTEGRAL EMERGENCY
			<b>NH</b> NATURAL HORN ACRYLIC	<b>BBR</b> BRUSHED BRASS	<b>40D26</b> 4@26W QD (10989.0)	<b>FUS</b> FUSED		
			<b>ET</b> ETRUSCAN ACRYLIC	<b>ABR</b> ANTIQUE BRASS	<b>4TT32</b> 4@32W TT (9529.0)	<b>TLP</b> TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)		
			<b>WS</b> WHITE SWIRL ACRYLIC	<b>STB</b> STATUARY BRONZE	<b>2BX39</b> 2@39W BX (13772.0)			
	<b>P1AH</b> PENDANT WITH 3 ANGLED STEMS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY 	33	<b>PTD</b> PAINTED - SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	<b>ORB</b> OIL RUBBED BRONZE	<b>33"</b>	<b>31N150</b> 3@150W IN (13742.0)	40	<b>CIB</b> CLEAR INNER BOWL
					<b>80D26</b> 8@26W QD (12189.0)	<b>ULD</b> UL DAMP LABEL		
	<b>P1ED</b> PENDANT WITH 3 ANGLED AIRCRAFT CABLES TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY 	41			<b>6BX39</b> 6@39W BX (8668.0)	<b>6BX40</b> 6@40W BX	50	<b>TRC</b> TRIPLE CIRCUIT
					<b>6BX50</b> 6@50W BX	<b>6BX55</b> 6@55W BX		<b>DNL</b> PAR DOWN LIGHT
					<b>6IN150</b> 6@150W IN (13743.0)			<b>BFL</b> BOTTOM FINIAL (SEE BELOW)
					<b>41"</b>			
					<b>8TT42</b> 8@42W TT (13749.0)			
					<b>9BX39</b> 9@39W BX			
					<b>9BX40</b> 9@40W BX			
					<b>9BX50</b> 9@50W BX (13747.0)			
	<b>9BX55</b> 9@55W BX							
		<b>8IN150</b> 8@150W IN (13744.0)						

↓ SPECIFY CATALOG CODE

SAMPLE CODE: **HR1-P1AE-26-GW-BAL-4TT32-120-30-DMA**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT [WWW.OCL.COM](http://WWW.OCL.COM)





- Fixture mounts to a standard 4" J-box (supplied by others), and features a 45-degree sloped-ceiling canopy.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.
- Bottom finial option increases overall height by length of the finial.

- For photometric data, please visit [www.ocl.com](http://www.ocl.com).
- For lamp and base information, see pages 496-505 in the reference section.
- Par down light option available in combination with a variety of compact fluorescent reflectors.
- For metal halide lamping contact factory.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.






**BFL**  
BOTTOM FINIAL

## HORIZON™ PENDANT



HR1-P1AA-26-WS-ORB



HR1-P1AH-26-GW-PBR

### MATCHING FIXTURES



page 340








page 450



page 486

### FEATURES

- The Horizon features a low-profile, minimalist square trim.
- A transitional design makes it a welcome addition to both contemporary and traditional applications.
- Spun from solid, non-ferrous 0.040" thick brass or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS	
 <p>HR1</p>	<b>P1AA</b> PENDANT WITH A SINGLE CENTER STEM 	16	<b>GW</b> GLOSS WHITE ACRYLIC	<b>PAL</b> POLISHED ALUMINUM	<b>16"</b>	<b>120</b>	21	<b>DMA</b> ADVANCE® DIMMING BALLAST	
			<b>MW</b> MATTE WHITE ACRYLIC	<b>BAL</b> BRUSHED ALUMINUM	<b>20D26</b> 2@26W QD (13771.0)	<b>277</b>		<b>DML</b> LUTRON® DIMMING BALLAST	
	<b>P1AE</b> PENDANT WITH 4 VERTICAL STEMS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY 	26	<b>FA</b> FAUX ALABASTER ACRYLIC	<b>PBR</b> POLISHED BRASS	<b>26"</b>	32	347	<b>EMI</b> INTEGRAL EMERGENCY	
			<b>NH</b> NATURAL HORN ACRYLIC	<b>BBR</b> BRUSHED BRASS	<b>40D26</b> 4@26W QD (10989.0)			<b>FUS</b> FUSED	
			<b>ET</b> ETRUSCAN ACRYLIC	<b>ABR</b> ANTIQUE BRASS	<b>4TT32</b> 4@32W TT (9529.0)			<b>TLP</b> TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)	
			<b>WS</b> WHITE SWIRL ACRYLIC	<b>STB</b> STATUARY BRONZE	<b>2BX39</b> 2@39W BX (13772.0)			<b>CIB</b> CLEAR INNER BOWL <b>ULD</b> UL DAMP LABEL <b>TRC</b> TRIPLE CIRCUIT <b>DNL</b> PAR DOWN LIGHT <b>BFL</b> BOTTOM FINIAL (SEE BELOW)	
	<b>PTD</b> PAINTED - SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	<b>3IN150</b> 3@150W IN (13742.0)	<b>3IN150</b> 3@150W IN (13742.0)						
	<b>P1AH</b> PENDANT WITH 3 ANGLED STEMS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY 	33	<b>WS</b> WHITE SWIRL ACRYLIC	<b>ORB</b> OIL RUBBED BRONZE	<b>33"</b>	40	50	<b>CIB</b> CLEAR INNER BOWL <b>ULD</b> UL DAMP LABEL <b>TRC</b> TRIPLE CIRCUIT <b>DNL</b> PAR DOWN LIGHT <b>BFL</b> BOTTOM FINIAL (SEE BELOW)	
					<b>80D26</b> 8@26W QD (12189.0)				<b>80D26</b> 8@26W QD (12189.0)
	<b>P1ED</b> PENDANT WITH 3 ANGLED AIRCRAFT CABLES TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY 	41	<b>WS</b> WHITE SWIRL ACRYLIC	<b>ORB</b> OIL RUBBED BRONZE	<b>41"</b>	50	50	<b>CIB</b> CLEAR INNER BOWL <b>ULD</b> UL DAMP LABEL <b>TRC</b> TRIPLE CIRCUIT <b>DNL</b> PAR DOWN LIGHT <b>BFL</b> BOTTOM FINIAL (SEE BELOW)	
					<b>6BX39</b> 6@39W BX (8668.0)				<b>6BX39</b> 6@39W BX (8668.0)
					<b>6BX40</b> 6@40W BX				<b>6BX40</b> 6@40W BX
					<b>6BX50</b> 6@50W BX				<b>6BX50</b> 6@50W BX
					<b>6BX55</b> 6@55W BX				<b>6BX55</b> 6@55W BX
					<b>6IN150</b> 6@150W IN (13743.0)				<b>6IN150</b> 6@150W IN (13743.0)
	<b>8TT42</b> 8@42W TT (13749.0)	<b>8TT42</b> 8@42W TT (13749.0)							
<b>9BX39</b> 9@39W BX	<b>9BX39</b> 9@39W BX								
<b>9BX40</b> 9@40W BX	<b>9BX40</b> 9@40W BX								
<b>9BX50</b> 9@50W BX (13747.0)	<b>9BX50</b> 9@50W BX (13747.0)								
<b>9BX55</b> 9@55W BX	<b>9BX55</b> 9@55W BX								
<b>8IN150</b> 8@150W IN (13744.0)	<b>8IN150</b> 8@150W IN (13744.0)								

↓ SPECIFY CATALOG CODE

SAMPLE CODE: **HR1-P1AH-26-GW-PBR-4TT32-120-30-DMA**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT [WWW.OCL.COM](http://WWW.OCL.COM)

- Fixture mounts to a standard 4" J-box (supplied by others), and features a 45-degree sloped-ceiling canopy.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.
- Bottom finial option increases overall height by length of the finial.

- For photometric data, please visit [www.ocl.com](http://www.ocl.com).
- For lamp and base information, see pages 496-505 in the reference section.
- Par down light option available in combination with a variety of compact fluorescent reflectors.
- For metal halide lamping contact factory.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.



**BFL**  
BOTTOM FINIAL