





HORIZON™ SCONCE



HR1-S1SA-16-GW-BAL

ADA



HR1-S1SB-16-WS-ORB

▾ MATCHING FIXTURES



page 60









page 450



page 486

▾ FEATURES

- The Horizon features a low-profile, minimalist square trim.
- A transitional design makes it a welcome piece for both contemporary and traditional applications.
- Spun from solid, non-ferrous 0.040" thick brass or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 HR1	S1SA INDOOR ADA COMPLIANT SCNCE 	16	GW GLOSS WHITE ACRYLIC MW MATTE WHITE ACRYLIC	PAL POLISHED ALUMINUM BAL BRUSHED ALUMINUM	16"  2QD13 2@13W QD (13793.0)	120 277	DMA ADVANCE® DIMMING BALLAST DML LUTRON® DIMMING BALLAST
		26	FA FAUX ALABASTER ACRYLIC NH NATURAL HORN ACRYLIC ET ETRUSCAN ACRYLIC WS WHITE SWIRL ACRYLIC	PTR PEWTER PBR POLISHED BRASS BBR BRUSHED BRASS ABR ANTIQUE BRASS STB STATUARY BRONZE SNK SATIN NICKEL ORB OIL RUBBED BRONZE PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	26"  2IN40 2@40W IN (13808.0) 2BX27 2@27W BX 2IN40 2@40W IN	347 FUS FUSED ULD UL DAMP LABEL TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)	
 HR1	S1SB INDOOR SCNCE 	16	GW GLOSS WHITE ACRYLIC MW MATTE WHITE ACRYLIC	PAL POLISHED ALUMINUM BAL BRUSHED ALUMINUM	16" 2QD13 2@13W QD (13809.0)	120 277	DMA ADVANCE® DIMMING BALLAST DML LUTRON® DIMMING BALLAST
		26	FA FAUX ALABASTER ACRYLIC NH NATURAL HORN ACRYLIC ET ETRUSCAN ACRYLIC WS WHITE SWIRL ACRYLIC	PTR PEWTER PBR POLISHED BRASS BBR BRUSHED BRASS ABR ANTIQUE BRASS STB STATUARY BRONZE SNK SATIN NICKEL ORB OIL RUBBED BRONZE PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	26" 2IN60 2@60W IN 2QD26 2@26W QD (12201.0) 2IN100 2@100W IN (13792.0)	347 FUS FUSED ULD UL DAMP LABEL TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)	

▾ SPECIFY CATALOG CODE

SAMPLE CODE: **HR1-S1SB-16-WS-ORB-2QD13-120-FUS**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- ADA compliant version available.
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.