


FIXTURE WEIGHT 5 LBS



FIXTURE WEIGHT 12 LBS




IC1-S1SA-11-GW-BNP

ADA




IC2-S1SA-11-GW-BAL

ADA



FIXTURE WEIGHT 5 LBS








FIXTURE WEIGHT 12 LBS



FEATURES

- The Icon sconce is offered in a variety of sizes and lamping packages.
- Available with stylish perforated aluminum overlay between the extruded aluminum vertical bars.
- 3/16" thick extruded virgin white acrylic diffuser is UV stable and UL-94 HB Flame Class rated.
- Faux acrylic is thermally formed and colors are mixed completely through to avoid noticeable fading.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 <p>IC1</p>  <p>IC2 (PERFORATED METAL)</p>	<p>S1SA INDOOR ADA COMPLIANT SCNCE</p> 	11	<p>GW GLOSS WHITE ACRYLIC</p> <p>MW MATTE WHITE ACRYLIC</p>	<p>PAL POLISHED ALUMINUM</p> <p>BAL BRUSHED ALUMINUM</p>	<p>11" </p> <p>2QD13 2@13W QD</p>	<p>120</p> <p>277</p>	<p>DMA ADVANCE® DIMMING BALLAST</p> <p>DML LUTRON® DIMMING BALLAST</p>
		16	<p>FA FAUX ALABASTER ACRYLIC</p> <p>NH NATURAL HORN ACRYLIC</p> <p>ET ETRUSCAN ACRYLIC</p> <p>WS WHITE SWIRL ACRYLIC</p>	<p>PTR PEWTER</p> <p>PBR POLISHED BRASS</p> <p>BBR BRUSHED BRASS</p> <p>ABR ANTIQUE BRASS</p> <p>STB STATUARY BRONZE</p> <p>SNK SATIN NICKEL</p> <p>ORB OIL RUBBED BRONZE</p> <p>PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>	<p>1QD26 1@26W QD (13785.0)</p> <p>2IN40 2@40W IN</p> <p>16" </p> <p>2BX27 2@27W BX (12404.0)</p> <p>2BX39 2@39W BX</p> <p>2IN60 2@60W IN</p>	<p>347</p>	<p>EMR REMOTE MOUNT EMERGENCY (11" SIZE ONLY)</p> <p>EMI INTEGRAL EMERGENCY (16" SIZE ONLY)</p> <p>FUS FUSED</p> <p>ULD UL DAMP LABEL</p>
<p>▾ SPECIFY CATALOG CODE</p>							

SAMPLE CODE: **IC2-S1SA-11-GW-BAL-1QD26-120-ULD**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Fixture is ADA compliant.
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.