


FIXTURE WEIGHT 6 LBS



FIXTURE WEIGHT 13 LBS



KD1-S1SA-12-HG-BAL

ADA







KD1-S1SA-12-FA-BAL

ADA



FEATURES

- The diffuser of the Kincaid sconce is held firmly between two decorative aluminum bars.
- Each bar is made from a machined aluminum extruded profile.
- Available with thermally formed acrylic or glass diffuser.
- Acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 <p>KD1</p>	<p>S1SA INDOOR ADA COMPLIANT SCONCE</p> 	<p>12 16</p>	<p>GW GLOSS WHITE ACRYLIC MW MATTE WHITE ACRYLIC FA FAUX ALABASTER ACRYLIC NH NATURAL HORN ACRYLIC ET ETRUSCAN ACRYLIC WS WHITE SWIRL ACRYLIC HG HONEYTHREAD GLASS</p>	<p>PAL POLISHED ALUMINUM BAL BRUSHED ALUMINUM PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>	<p>12"  1BX18 1@18W BX (13801.0) 16"  1BX27 1@27W BX</p>	<p>120 277 347</p>	<p>DMA ADVANCE® DIMMING BALLAST DML LUTRON® DIMMING BALLAST EMR REMOTE MOUNT EMERGENCY FUS FUSED ULD UL DAMP LABEL</p>
<p>↓ SPECIFY CATALOG CODE</p>							

SAMPLE CODE: **KD1-S1SA-12-FA-BAL-1BX18-120-ULD**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Fixture is ADA compliant.
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.