

FIXTURE WEIGHT 9 LBS



LU1-P1CA-07-WG-BAL



**FEATURES**

- The Luma was inspired by the elegance of a champagne glass.
- All the pieces of the Luma meld together to create a beautifully simple composition.
- The simple shape of the hand-blown glass continues into the aluminum trim, designed to hold it with no visible hardware.
- Features hand-blown white glass with a minimum wall thickness of 0.1875".
- Tool-less access to lamp.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent lamping options.
- Contact factory for additional modifications or options.


SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS
 <p>LU1</p>	<p><b>P1CA</b> PENDANT WITH A SINGLE POWER CORD</p> 	<p><b>07</b></p>	<p><b>WG</b> WHITE GLASS</p>	<p><b>PAL</b> POLISHED ALUMINUM <b>BAL</b> BRUSHED ALUMINUM <b>PTD</b> PAINTED - SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>	<p><b>7"</b> <b>1BX18</b> 1@18W BX <b>1BX27</b> 1@27W BX <b>1BX39</b> 1@39W BX (13791.0)</p>	<p><b>120</b> <b>277</b> <b>347</b></p>	<p><b>34</b></p>	<p><b>DMA</b> ADVANCE® DIMMING BALLAST <b>EMI</b> INTEGRAL EMERGENCY REQUIRES 12" BALLAST CANOPY (SEE BELOW) <b>FUS</b> FUSED <b>ULD</b> UL DAMP LABEL</p>
<p>▾ SPECIFY CATALOG CODE</p>								

SAMPLE CODE: LU1-P1CA-07-WG-BAL-1BX27-120-34-FUS

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Maximum overall height subject to ballast specification. Consult factory for details.

- For photometric data, please visit [www.ocl.com](http://www.ocl.com).
- For lamp and base information, see pages 496-505 in the reference section.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.



**EMI**  
INTEGRAL EMERGENCY REQUIRES 12" BALLAST CANOPY