


MR1-C1NA-17-GW-BBR



MR2-C1NA-17-FA-ABR

▼ MATCHING FIXTURES



page 166



page 166






page 300



page 300

▼ FEATURES

- The trim ring of the Mirage features two unique architectural banding designs. Choose from either Egg-and-Dart or Greek Key banding.
- Its transitional design makes the Mirage a welcome piece for both contemporary and traditional applications.
- Spun from solid, non-ferrous 0.040" thick brass, or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 <p>MR1 (GREEK KEY)</p>  <p>MR2 (EGG-AND-DART)</p>	<p>C1NA SURFACE CEILING MOUNT</p> 	17	<p>GW GLOSS WHITE ACRYLIC</p> <p>MW MATTE WHITE ACRYLIC</p>	<p>PAL POLISHED ALUMINUM</p> <p>BAL BRUSHED ALUMINUM</p>	<p>17"</p> <p>2QD13 2@13W QD (13789.0)</p> <p>2QD26 2@26W QD (12190.0)</p>	<p>120</p> <p>277</p>	<p>DMA ADVANCE® DIMMING BALLAST</p> <p>DML LUTRON® DIMMING BALLAST</p>
		27	<p>FA FAUX ALABASTER ACRYLIC</p> <p>NH NATURAL HORN ACRYLIC</p> <p>ET ETRUSCAN ACRYLIC</p> <p>WS WHITE SWIRL ACRYLIC</p>	<p>PTR PEWTER</p> <p>PBR POLISHED BRASS</p> <p>BBR BRUSHED BRASS</p> <p>ABR ANTIQUE BRASS</p> <p>STB STATUARY BRONZE</p> <p>SNK SATIN NICKEL</p> <p>ORB OIL RUBBED BRONZE</p> <p>PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>	<p>2IN60 2@60W IN</p> <p>27"</p> <p>2QD26 2@26W QD (13812.0)</p> <p>4QD26 4@26W QD (12205.0)</p> <p>2IN100 2@100W IN</p>	<p>347</p>	<p>EMR REMOTE MOUNT EMERGENCY (17" SIZE ONLY)</p> <p>EMI INTEGRAL EMERGENCY (27" SIZE ONLY)</p> <p>FUS FUSED</p> <p>ULD UL DAMP LABEL</p> <p>VOL "V" STYLE OVERLAY AND BOTTOM FINIAL</p> <p>OOL "O" STYLE OVERLAY AND BOTTOM FINIAL</p>

▾ SPECIFY CATALOG CODE

SAMPLE CODE: **MR2-C1NA-17-FA-ABR-2QD13-120-ULD**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others) and may require additional anchors on larger sizes.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.