




MIRAGE™ PENDANT




FIXTURE WEIGHT 20 LBS



FIXTURE WEIGHT 32 LBS



FIXTURE WEIGHT 42 LBS




FIXTURE WEIGHT 52 LBS




MR1-P1AA-27-GW-SGP/SNK




MR1-P1AH-27-GW-BBR




FIXTURE WEIGHT 20 LBS



FIXTURE WEIGHT 32 LBS



FIXTURE WEIGHT 42 LBS



FIXTURE WEIGHT 52 LBS

MATCHING FIXTURES



page 300



page 438

FEATURES

- The trim ring of the Mirage features two unique architectural banding designs. Choose from either Egg-and-Dart or Greek Key banding.
- Spun from solid, non-ferrous 0.040" thick brass, or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS	
<p>MR1 (GREEK KEY BANDING)</p> <p>MR2 (EGG-AND-DART BANDING)</p>	P1AA PENDANT WITH A SINGLE CENTER STEM 	17	GW GLOSS WHITE ACRYLIC MW MATTE WHITE ACRYLIC	PAL POLISHED ALUMINUM BAL BRUSHED ALUMINUM	17" 4QD26 4@26W QD (10989.0) 2IN100 2@100W IN (7135.0)	120 277 347	24	DMA ADVANCE® DIMMING BALLAST DML LUTRON® DIMMING BALLAST	
			P1AH PENDANT WITH 3 ANGLED STEMS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY 	27	FA FAUX ALABASTER ACRYLIC NH NATURAL HORN ACRYLIC	PBR POLISHED BRASS BBR BRUSHED BRASS ABR ANTIQUE BRASS	27" 4TT32 4@32W TT (9529.0) 4TT42 4@42W TT	32	EMI INTEGRAL EMERGENCY FUS FUSED
					P1AI PENDANT WITH 3 ANGLED REEDED STEMS TO COLLECTOR AND A SINGLE REEDED CENTER STEM FROM TRIM RING TO CANOPY 	34	ET ETRUSCAN ACRYLIC WS WHITE SWIRL ACRYLIC	STB STATUARY BRONZE SNK SATIN NICKEL ORB OIL RUBBED BRONZE PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	34" 8QD26 8@26W QD (12189.0) 6BX40 6@40W BX 6BX50 6@50W BX (9531.0) 6BX55 6@55W BX 8BX39 8@39W BX (12187.0) 3IN200 3@200W IN
	42	8TT42 8@42W TT (13749.0) 9BX39 9@39W BX 9BX40 9@40W BX 9BX50 9@50W BX (13747.0) 9BX55 9@55W BX 8IN150 8@150W IN (13744.0)					50	OOL "O" STYLE OVERLAY AND BOTTOM FINIAL	


☑ SPECIFY CATALOG CODE

SAMPLE CODE: **MR1-P1AH-27-GW-BBR-4TT32-120-30-TLP**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM


- Fixture mounts to a standard 4" J-box (supplied by others), and features a 45-degree sloped-ceiling canopy.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.
- Bottom finial option increases overall height by length of the finial.

- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- Par down light option available in combination with a variety of compact fluorescent reflectors.
- For metal halide lamping contact factory.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.




BFL
BOTTOM FINIAL


MIRAGE™ PENDANT




FIXTURE WEIGHT 20 LBS



FIXTURE WEIGHT 32 LBS



FIXTURE WEIGHT 42 LBS




FIXTURE WEIGHT 52 LBS




MR2-P1AH-27-GW-PBR




MR2-P1AI-27-FA-ABR




FIXTURE WEIGHT 20 LBS



FIXTURE WEIGHT 32 LBS



FIXTURE WEIGHT 42 LBS



FIXTURE WEIGHT 52 LBS

MATCHING FIXTURES



page 300



page 438

FEATURES

- The trim ring of the Mirage features two unique architectural banding designs. Choose from either Egg-and-Dart or Greek Key banding.
- Spun from solid, non-ferrous 0.040" thick brass, or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.


SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS	
<p>MR1 (GREEK KEY BANDING)</p> <p>MR2 (EGG-AND-DART BANDING)</p>	P1AA PENDANT WITH A SINGLE CENTER STEM 	17	GW GLOSS WHITE ACRYLIC MW MATTE WHITE ACRYLIC	PAL POLISHED ALUMINUM BAL BRUSHED ALUMINUM PTR PEWTER	17" 4QD26 4@26W QD (10989.0) 2IN100 2@100W IN (7135.0)	120 277 347	24	DMA ADVANCE® DIMMING BALLAST DML LUTRON® DIMMING BALLAST	
			P1AH PENDANT WITH 3 ANGLED STEMS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY 	FA FAUX ALABASTER ACRYLIC NH NATURAL HORN ACRYLIC ET ETRUSCAN ACRYLIC	PBR POLISHED BRASS BBR BRUSHED BRASS ABR ANTIQUE BRASS STB STATUARY BRONZE SNK SATIN NICKEL	27" 4TT32 4@32W TT (9529.0) 4TT42 4@42W TT 4BX39 4@39W BX (8222.1) 3IN150 3@150W IN (13742.0)	32	EMI INTEGRAL EMERGENCY FUS FUSED	
				P1AI PENDANT WITH 3 ANGLED REEDED STEMS TO COLLECTOR AND A SINGLE REEDED CENTER STEM FROM TRIM RING TO CANOPY 	WS WHITE SWIRL ACRYLIC	ORB OIL RUBBED BRONZE PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	34" 8QD26 8@26W QD (12189.0) 6BX40 6@40W BX 6BX50 6@50W BX (9531.0) 6BX55 6@55W BX 8BX39 8@39W BX (12187.0) 3IN200 3@200W IN 42" 8TT42 8@42W TT (13749.0) 9BX39 9@39W BX 9BX40 9@40W BX 9BX50 9@50W BX (13747.0) 9BX55 9@55W BX 8IN150 8@150W IN (13744.0)	40 50	CIB CLEAR INNER BOWL ULD UL DAMP LABEL TRC TRIPLE CIRCUIT BFL BOTTOM FINIAL (SEE BELOW) DNL PAR DOWN LIGHT VOL "V" STYLE OVERLAY AND BOTTOM FINIAL OOL "O" STYLE OVERLAY AND BOTTOM FINIAL
	42								
	<p> SPECIFY CATALOG CODE </p>								

SAMPLE CODE: **MR2-P1AI-27-FA-ABR-4TT32-120-30-TLP**

PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others), and features a 45-degree sloped-ceiling canopy.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.
- Bottom finial option increases overall height by length of the finial.

- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- Par down light option available in combination with a variety of compact fluorescent reflectors.
- For metal halide lamping contact factory.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.



BFL
BOTTOM FINIAL