





MIRAGE™ SCNCE



MR1-S1SB-17-GW-SGP/SNK



MR2-S1SB-17-GW-PBR

▼ MATCHING FIXTURES



page 166



page 166






page 438



page 438

▼ FEATURES

- The trim ring of the Mirage features two unique architectural banding designs. Choose from either Egg-and-Dart or Greek Key banding.
- Spun from solid, non-ferrous 0.040" thick brass, or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 <b>MR1</b> (GREEK KEY BANDING)	<b>S1SB</b> INDOOR SCONCE 	<b>17</b>	<b>GW</b> GLOSS WHITE ACRYLIC	<b>PAL</b> POLISHED ALUMINUM	<b>17"</b>	<b>120</b>	<b>DMA</b> ADVANCE® DIMMING BALLAST
			<b>MW</b> MATTE WHITE ACRYLIC	<b>BAL</b> BRUSHED ALUMINUM			<b>20D26</b> 2@26W QD (12201.0)
 <b>MR2</b> (EGG-AND-DART BANDING)		<b>27</b>	<b>FA</b> FAUX ALABASTER ACRYLIC	<b>PTR</b> PEWTER	<b>27"</b>	<b>347</b>	<b>EMR</b> REMOTE MOUNT EMERGENCY (17" SIZE ONLY)
			<b>NH</b> NATURAL HORN ACRYLIC	<b>PBR</b> POLISHED BRASS			<b>2TT32</b> 2@32W TT (13807.0)
			<b>ET</b> ETRUSCAN ACRYLIC	<b>BBR</b> BRUSHED BRASS	<b>2IN100</b> 2@100W IN (13792.0)		<b>FUS</b> FUSED
			<b>WS</b> WHITE SWIRL ACRYLIC	<b>ABR</b> ANTIQUE BRASS			<b>ULD</b> UL DAMP LABEL
			<b>PTD</b> PAINTED - SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	<b>STB</b> STATUARY BRONZE			<b>TLP</b> TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)
				<b>SNK</b> SATIN NICKEL			<b>VOL</b> "V" STYLE OVERLAY AND BOTTOM FINIAL
				<b>ORB</b> OIL RUBBED BRONZE			<b>OOL</b> "O" STYLE OVERLAY AND BOTTOM FINIAL

☐ SPECIFY CATALOG CODE

SAMPLE CODE: **MR2-S1SB-17-GW-PBR-20D26-120-ULD**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT [WWW.OCL.COM](http://WWW.OCL.COM)

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- For photometric data, please visit [www.ocl.com](http://www.ocl.com).
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.