


MONACO™ CEILING



MN1-C1NA-16-GW-PBR

MATCHING FIXTURES



page 108



page 112





page 326



page 480

FEATURES

- The Monaco features a shallow acrylic diffuser accented by a rolled brass or aluminum ring.
- Constructed with solid, non-ferrous brass or aluminum.
- Its transitional design makes the Monaco a welcome piece for both contemporary and traditional applications.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 MN1	C1NA SURFACE CEILING MOUNT 	16	GW GLOSS WHITE ACRYLIC	PAL POLISHED ALUMINUM	16"	120	DMA ADVANCE® DIMMING BALLAST
		19	MW MATTE WHITE ACRYLIC	BAL BRUSHED ALUMINUM	2QD13 2@13W QD (13789.0)	277	DML LUTRON® DIMMING BALLAST
		23	FA FAUX ALABASTER ACRYLIC	PTR PEWTER	19"	347	EMR REMOTE MOUNT EMERGENCY
			NH NATURAL HORN ACRYLIC	PBR POLISHED BRASS	2QD26 2@26W QD (12190.0)		FUS FUSED
			ET ETRUSCAN ACRYLIC	BBR BRUSHED BRASS	23"		ULD UL DAMP LABEL
			WS WHITE SWIRL ACRYLIC	ABR ANTIQUE BRASS	2QD26 2@26W QD (13812.0)		
				STB STATUARY BRONZE	4QD26 4@26W QD (12205.0)		
			SNK SATIN NICKEL				
			ORB OIL RUBBED BRONZE				
			PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)				

▾ SPECIFY CATALOG CODE

SAMPLE CODE: **MN1-C1NA-16-GW-PBR-2QD13-120-FUS**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others) and may require additional anchors on larger sizes.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.