




MONACO™ PENDANT




FIXTURE WEIGHT 25 LBS



FIXTURE WEIGHT 30 LBS



FIXTURE WEIGHT 35 LBS




FIXTURE WEIGHT 45 LBS




MN1-P1AH-23-GW-PBR




MN1-P1ED-23-GW-SMP




FIXTURE WEIGHT 25 LBS



FIXTURE WEIGHT 30 LBS



FIXTURE WEIGHT 35 LBS



FIXTURE WEIGHT 45 LBS

MATCHING FIXTURES



page 112



page 326







page 460



page 480

FEATURES

- The Monaco features a shallow acrylic diffuser accented by a rolled brass or aluminum ring.
- Available in diameters up to 72".
- Constructed with solid, non-ferrous brass or aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

| SERIES   | HANGING SYSTEM  | SIZE   | DIFFUSER                         | FINISH   | LAMPING (PHOTOMETRIC TEST #)    | VOLTAGE                              | OAH<br>SPECIFY IN INCHES  | OPTIONS                             |   |
|--|---|--|----------------------------------|--|---------------------------------|--------------------------------------|---------------------------|-------------------------------------|---|
|  <p>MN1</p> | <b>P1AH</b> PENDANT WITH 3 ANGLED STEMS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY   | 23   | <b>GW</b> GLOSS WHITE ACRYLIC    | <b>PAL</b> POLISHED ALUMINUM   | <b>23"</b>                      | <b>120</b>                           | 30                        | <b>DMA</b> ADVANCE® DIMMING BALLAST |   |
|  |   |  | <b>MW</b> MATTE WHITE ACRYLIC    | <b>BAL</b> BRUSHED ALUMINUM  | <b>4QD26</b> 4@26W QD (10989.0) | <b>277</b>                           |                           | <b>DML</b> LUTRON® DIMMING BALLAST  |   |
|  |   |  | <b>FA</b> FAUX ALABASTER ACRYLIC | <b>PTR</b> PEWTER  | <b>4TT32</b> 4@32W TT (9529.0)  | <b>347</b>                           |                           | <b>EMI</b> INTEGRAL EMERGENCY       |   |
|  |   | <b>P1ED</b> PENDANT WITH 3 ANGLED AIRCRAFT CABLES TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY  | 30                               | <b>FA</b> FAUX ALABASTER ACRYLIC   | <b>PBR</b> POLISHED BRASS       | <b>3IN150</b> 3@150W IN (13742.0)    | 30"                       | 36                                  | <b>EMI</b> INTEGRAL EMERGENCY                               |
|  |   |  |                                  | <b>NH</b> NATURAL HORN ACRYLIC   | <b>BBR</b> BRUSHED BRASS        | <b>8QD26</b> 8@26W QD (12189.0)      |                           |                                     | <b>FUS</b> FUSED  |
|  |   |  |                                  | <b>ET</b> ETRUSCAN ACRYLIC   | <b>ABR</b> ANTIQUE BRASS        | <b>4BX39</b> 4@39W BX (9640.0)       |                           |                                     | <b>TLP</b> TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT) |
|  | <b>P16B</b> PENDANT WITH 3 BEADED CHAINS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY  |  | 36                               | <b>WS</b> WHITE SWIRL ACRYLIC  | <b>PBR</b> POLISHED BRASS       | <b>3IN150</b> 3@150W IN (13742.0)    | 30"                       | 36                                  | <b>FUS</b> FUSED  |
|  |   |  |                                  | <b>PTD</b> PAINTED - SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS) | <b>ABR</b> ANTIQUE BRASS        | <b>4BX39</b> 4@39W BX (8668.0)       |                           |                                     | <b>ULD</b> UL DAMP LABEL                                    |
|  |   |  |                                  | <b>ORB</b> OIL RUBBED BRONZE   | <b>STB</b> STATUARY BRONZE      | <b>6BX39</b> 6@39W BX (13743.0)      |                           |                                     | <b>TRC</b> TRIPLE CIRCUIT                                   |
|  |   | 42   | 36                               | <b>PTD</b> PAINTED - SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS) | <b>ORB</b> OIL RUBBED BRONZE    | <b>6IN150</b> 6@150W IN (13743.0)    | 36"                       | 42                                  | <b>TRC</b> TRIPLE CIRCUIT                                   |
|  |   |  |                                  |  | <b>8TT32</b> 8@32W TT (13746.0) | <b>DNL</b> PAR DOWN LIGHT            |                           |                                     |   |
|  |   |  |                                  |  | <b>6BX40</b> 6@40W BX           | <b>BFL</b> BOTTOM FINIAL (SEE BELOW) |                           |                                     |   |
| 42   | <b>PTD</b> PAINTED - SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)  |  | <b>ORB</b> OIL RUBBED BRONZE     | <b>6IN150</b> 6@150W IN (13743.0)  | 42"                             | 48                                   | <b>TRC</b> TRIPLE CIRCUIT |                                     |   |
|  |   |  | <b>9BX39</b> 9@39W BX            | <b>DNL</b> PAR DOWN LIGHT  |                                 |                                      |                           |                                     |   |
|  |   |  | <b>9BX40</b> 9@40W BX            | <b>BFL</b> BOTTOM FINIAL (SEE BELOW)   |                                 |                                      |                           |                                     |   |

↓ SPECIFY CATALOG CODE

SAMPLE CODE: **MN1-P1ED-23-GW-SMP-4TT32-120-30-ULD**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT [WWW.OCL.COM](http://WWW.OCL.COM)





- Fixture mounts to a standard 4" J-box (supplied by others), and features a 45-degree sloped-ceiling canopy.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.
- Bottom finial option increases overall height by length of the finial.

- For photometric data, please visit [www.ocl.com](http://www.ocl.com).
- For lamp and base information, see pages 496-505 in the reference section.
- Par down light option available in combination with a variety of compact fluorescent reflectors.
- For metal halide lamping contact factory.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.



**BFL**  
BOTTOM FINIAL

MONACO™ PENDANT



MN1-P1GB-23-GW-BAL



LOCATION: Dr. CC and Mabel L. Criss Library, University of Nebraska, Omaha, NE ENGINEER: Alvine Engineering

MATCHING FIXTURES



page 112



page 326








page 460



page 480

FEATURES

- The Monaco features a shallow acrylic diffuser accented by a rolled brass or aluminum ring.
- Available in diameters up to 72".
- Constructed with solid, non-ferrous brass or aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

| SERIES  | HANGING SYSTEM  | SIZE   | DIFFUSER   | FINISH                            | LAMPING (PHOTOMETRIC TEST #)      | VOLTAGE                        | OAH<br>SPECIFY IN INCHES | OPTIONS   |
|---|---|--|--|-----------------------------------|-----------------------------------|--------------------------------|--------------------------|---|
|  <p>MN1</p>  | <b>P1AH</b> PENDANT WITH 3 ANGLED STEMS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY   | 23   | <b>GW</b> GLOSS WHITE ACRYLIC  | <b>PAL</b> POLISHED ALUMINUM      | <b>23"</b>                        | <b>120</b>                     | 30                       | <b>DMA</b> ADVANCE® DIMMING BALLAST<br><b>DML</b> LUTRON® DIMMING BALLAST<br><b>EMI</b> INTEGRAL EMERGENCY<br><b>FUS</b> FUSED<br><b>TLP</b> TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)<br><b>ULD</b> UL DAMP LABEL<br><b>TRC</b> TRIPLE CIRCUIT<br><b>DNL</b> PAR DOWN LIGHT<br><b>BFL</b> BOTTOM FINIAL (SEE BELOW) |
|   |   |  | <b>MW</b> MATTE WHITE ACRYLIC  | <b>BAL</b> BRUSHED ALUMINUM       | <b>4QD26</b> 4@26W QD (10989.0)   | <b>277</b>                     |                          |   |
|   |   |  | <b>FA</b> FAUX ALABASTER ACRYLIC   | <b>PTR</b> PEWTER                 | <b>4TT32</b> 4@32W TT (9529.0)    | <b>347</b>                     |                          |   |
|   |   | <b>P1ED</b> PENDANT WITH 3 ANGLED AIRCRAFT CABLES TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY  | 30   | <b>PBR</b> POLISHED BRASS         | <b>3IN150</b> 3@150W IN (13742.0) | <b>30"</b>                     | 36                       |   |
|   |   |  |  | <b>BBR</b> BRUSHED BRASS          | <b>8QD26</b> 8@26W QD (12189.0)   | <b>4BX39</b> 4@39W BX (9640.0) |                          |   |
|   |   |  |  | <b>NH</b> NATURAL HORN ACRYLIC    | <b>ABR</b> ANTIQUE BRASS          | <b>6BX39</b> 6@39W BX (8668.0) |                          |   |
|   | <b>P1GB</b> PENDANT WITH 3 BEADED CHAINS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY  | 36   | <b>ET</b> ETRUSCAN ACRYLIC   | <b>STB</b> STATUARY BRONZE        | <b>6IN150</b> 6@150W IN (13743.0) | 42                             |                          |   |
|   |   |  | <b>SNK</b> SATIN NICKEL  | <b>ORB</b> OIL RUBBED BRONZE      | <b>36"</b>                        |                                |                          |   |
|   |   |  | <b>PTD</b> PAINTED - SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS) | <b>8TT32</b> 8@32W TT (13746.0)   | 48                                |                                |                          |   |
|   |   |  | <b>6BX40</b> 6@40W BX  | <b>6BX50</b> 6@50W BX (13745.0)   |                                   |                                |                          |   |
|   |   |  | <b>6BX55</b> 6@55W BX  | <b>6IN150</b> 6@150W IN (13743.0) |                                   |                                |                          |   |
|   |   |  | <b>9BX39</b> 9@39W BX  | <b>9BX40</b> 9@40W BX             |                                   |                                |                          |   |
| <b>P1GB</b> PENDANT WITH 3 BEADED CHAINS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY  | 42  | <b>9BX50</b> 9@50W BX (13747.0)  | <b>9BX55</b> 9@55W BX  | <b>8IN150</b> 8@150W IN (13744.0) |                                   |                                |                          |   |

↓ SPECIFY CATALOG CODE

SAMPLE CODE: **MN1-P1GB-23-GW-BAL-4TT32-120-30-DMA**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT [WWW.OCL.COM](http://WWW.OCL.COM)

- Fixture mounts to a standard 4" J-box (supplied by others), and features a 45-degree sloped-ceiling canopy.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.
- Bottom finial option increases overall height by length of the finial.

- For photometric data, please visit [www.ocl.com](http://www.ocl.com).
- For lamp and base information, see pages 496-505 in the reference section.
- Par down light option available in combination with a variety of compact fluorescent reflectors.
- For metal halide lamping contact factory.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.



**BFL**  
BOTTOM FINIAL