



MONOLITH™ OUTDOOR SCONCE



ML1-010B-18-GW-SMP



ML5-010B-18-GW-BNP

▼ MATCHING FIXTURES



page 238

▼ FEATURES

- The Monolith sconce features a patterned metal face with a white acrylic diffuser.
- This contemporary sconce features three unique face designs. Consult factory for modified or custom designs.
- Back box is formed from 0.080" thick aluminum.
- Decorative face is formed from 0.064" thick aluminum.
- F1 rated, fully-enclosed acrylic diffuser.
- Virgin white acrylic is UV stable and UL-94 HB Flame Class rated.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 <p>ML1</p>  <p>ML4</p>  <p>ML5</p>	<p>010B OUTDOOR SCONCE</p> 	<p>18</p>	<p>GW GLOSS WHITE ACRYLIC</p>	<p>PTD PAINTED - SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>	<p>18"</p> <p>2QD13 2@13W QD</p> <p>2QD26 2@26W QD [12339.0]</p> <p>1BX27 1@27W BX</p> <p>1BX39 1@39W BX</p> <p>2IN60 2@60W IN [13783.0]</p>	<p>120</p> <p>277</p> <p>347</p>	<p>DMA ADVANCE® DIMMING BALLAST</p> <p>DML LUTRON® DIMMING BALLAST</p> <p>EMR REMOTE MOUNT EMERGENCY</p> <p>FUS FUSED</p>
<p>▾ SPECIFY CATALOG CODE</p>							


SAMPLE CODE: **ML5-010B-18-GW-BNP-1BX27-120**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT [WWW.OCL.COM](http://WWW.OCL.COM)

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating, 0°F/ -18°C starting temperature (3-5 year ballast warranty depending on ballast specification).
- For photometric data, please visit [www.ocl.com](http://www.ocl.com).
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.

OUTDOOR

## MONOLITH™ OUTDOOR SCONCE



ML4-010B-18-GW-SAP



LOCATION: South Coast Home Furnishings Centre, Costa Mesa, CA ARCHITECT: Lee & Sakahara Architects

### ▼ MATCHING FIXTURES



page 238

### ▼ FEATURES

- The Monolith sconce features a patterned metal face with a white acrylic diffuser.
- This contemporary sconce features three unique face designs. Consult factory for modified or custom designs.
- Back box is formed from 0.080" thick aluminum.
- Decorative face is formed from 0.064" thick aluminum.
- F1 rated, fully-enclosed acrylic diffuser.
- Virgin white acrylic is UV stable and UL-94 HB Flame Class rated.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 <p>ML1</p>  <p>ML4</p>  <p>ML5</p>	<p>010B OUTDOOR SCONCE</p> 	<p>18</p>	<p>GW GLOSS WHITE ACRYLIC</p>	<p>PTD PAINTED – SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>	<p>18"</p> <p>20D13 2@13W QD</p> <p>20D26 2@26W QD [12339.0]</p> <p>1BX27 1@27W BX</p> <p>1BX39 1@39W BX</p> <p>2IN60 2@60W IN [13783.0]</p>	<p>120</p> <p>277</p> <p>347</p>	<p>DMA ADVANCE® DIMMING BALLAST</p> <p>DML LUTRON® DIMMING BALLAST</p> <p>EMR REMOTE MOUNT EMERGENCY</p> <p>FUS FUSED</p>
<p>▾ SPECIFY CATALOG CODE</p>							

SAMPLE CODE: **ML4-010B-18-GW-SAP-1BX27-120**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT [WWW.OCL.COM](http://WWW.OCL.COM)

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating, 0°F/ -18°C starting temperature (3-5 year ballast warranty depending on ballast specification).
- For photometric data, please visit [www.ocl.com](http://www.ocl.com).
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.

OUTDOOR