



MONTAGE™ SCNCE



FIXTURE WEIGHT 5 LBS



FIXTURE WEIGHT 10 LBS









MG2-S1SA-11-GW-SMP

ADA



FEATURES

- The Montage sconce features a patterned metal face with a formed acrylic diffuser.
- This contemporary sconce features three unique face designs. Consult factory for modified or custom designs.
- Extruded virgin white acrylic is UV stable and UL-94 HB Flame Class rated.
- Faux acrylic is thermally formed and colors are mixed completely through to avoid noticeable fading.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.


SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 M61  M62  M63	S1SA INDOOR ADA COMPLIANT SCONCE 	11	GW GLOSS WHITE ACRYLIC MW MATTE WHITE ACRYLIC	PTD PAINTED – SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	11"  2QD13 2@13W QD (11631.0) 2IN40 2@40W IN (13779.0)	120 277 347	DMA ADVANCE® DIMMING BALLAST DML LUTRON® DIMMING BALLAST EMR REMOTE MOUNT EMERGENCY (11" SIZE ONLY) EMI INTEGRAL EMERGENCY (13" SIZE ONLY) FUS FUSED ULD UL DAMP LABEL TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT) BLP BOTTOM LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)
		13	FA FAUX ALABASTER ACRYLIC NH NATURAL HORN ACRYLIC ET ETRUSCAN ACRYLIC WS WHITE SWIRL ACRYLIC		13"  1BX18 1@18W BX (12390.0) 2QD26 2@26W QD 2IN40 2@40W IN		

☑ SPECIFY CATALOG CODE


SAMPLE CODE: **M62-S1SA-11-GW-SMP-2QD13-120-TLP-BLP**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Fixture is ADA compliant.
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.



FIXTURE WEIGHT 5 LBS



FIXTURE WEIGHT 10 LBS




MG1-S1SA-11-GW-BMP

ADA




MG3-S1SA-11-GW-GRP

ADA



FIXTURE WEIGHT 5 LBS









FIXTURE WEIGHT 10 LBS



FEATURES

- The Montage sconce features a patterned metal face with a formed acrylic diffuser.
- This contemporary sconce features three unique face designs. Consult factory for modified or custom designs.
- Extruded virgin white acrylic is UV stable and UL-94 HB Flame Class rated.
- Faux acrylic is thermally formed and colors are mixed completely through to avoid noticeable fading.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 M61  M62  M63	S1SA INDOOR ADA COMPLIANT SCNCE 	11	GW GLOSS WHITE ACRYLIC MW MATTE WHITE ACRYLIC	PTD PAINTED – SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	11"  2QD13 2@13W QD (11631.0) 2IN40 2@40W IN (13779.0)	120 277 347	DMA ADVANCE® DIMMING BALLAST DML LUTRON® DIMMING BALLAST EMR REMOTE MOUNT EMERGENCY (11" SIZE ONLY) EMI INTEGRAL EMERGENCY (13" SIZE ONLY) FUS FUSED ULD UL DAMP LABEL TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT) BLP BOTTOM LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)
		13	FA FAUX ALABASTER ACRYLIC NH NATURAL HORN ACRYLIC ET ETRUSCAN ACRYLIC WS WHITE SWIRL ACRYLIC		13"  1BX18 1@18W BX (12390.0) 2QD26 2@26W QD 2IN40 2@40W IN		

☑ SPECIFY CATALOG CODE

SAMPLE CODE: **M63-S1SA-11-GW-GRP-2QD13-120-ULD**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Fixture is ADA compliant.
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.