




FIXTURE WEIGHT 7 LBS



FIXTURE WEIGHT 9 LBS



FIXTURE WEIGHT 11 LBS



FIXTURE WEIGHT 13 LBS



NP1-S1SA-24-GW-BKP









▾ MATCHING FIXTURES



page 386

▾ FEATURES

- The Newport sconce features solid aluminum die-cast ends with a domed top and a distinctive tapering arch design.
- 0.125" thick, matte anodized, aluminum extruded back channel.
- 3/16" thick extruded virgin white acrylic is 45% DR high impact, UV stable, F1 rated, and UL-94 HB Flame Class rated.
- Newport can be mounted vertically or horizontally.
- Hinged front face simplifies re-lamping and maintenance.
- 21 standard powder coat paints offered, however all RAL colors available.
- Utilizes highly efficient, long lasting and low mercury T5 or T5HO lamps for minimal fixture maintenance and lamp disposal.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS		
 NP1	<b>S1SA</b> INDOOR ADA COMPLIANT SCNCE 	18	<b>GW</b> GLOSS WHITE ACRYLIC	PTD PAINTED - SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	18" 	120	<b>DMA</b> ADVANCE® DIMMING BALLAST		
			<b>MW</b> MATTE WHITE ACRYLIC		<b>1BX27</b> 1@27W BX		277	<b>DML</b> LUTRON® DIMMING BALLAST	
		24				24" 	347	<b>1BX39</b> 1@39W BX (13796.0)	<b>EMR</b> REMOTE MOUNT EMERGENCY (18" SIZE ONLY)
						<b>2LF14</b> 2@14W T5		<b>EMI</b> INTEGRAL EMERGENCY (24"/36"/48" SIZES ONLY)	
		36				36" 		<b>2LF24</b> 2@24W T5H0 (13797.0)	<b>ULD</b> UL DAMP LABEL
						<b>1BX40</b> 1@40W BX		<b>FUS</b> FUSED	
		48				48" 		<b>1BX50</b> 1@50W BX	
						<b>1BX55</b> 1@55W BX			
								<b>2LF21</b> 2@21W T5	
								<b>2LF39</b> 2@39W T5H0 (13798.0)	
								<b>2BX39</b> 2@39W BX	
								<b>2LF28</b> 2@28W T5	
					<b>2LF54</b> 2@54W T5H0 (13799.0)				
					<b>2BX40</b> 2@40W BX				
					<b>2BX50</b> 2@50W BX				
					<b>2BX55</b> 2@55W BX				

▾ SPECIFY CATALOG CODE

SAMPLE CODE: NP1-S1SA-24-GW-BKP-2LF14-120-DML

↑ PHOTOMETRIC INFORMATION AVAILABLE AT [WWW.OCL.COM](http://WWW.OCL.COM)

- Fixture mounts to a standard 4" J-box (supplied by others), and requires additional anchors.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).

- Fixture is ADA compliant.
- For photometric data, please visit [www.ocl.com](http://www.ocl.com).
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.