




NIMBUS™ PENDANT



FIXTURE WEIGHT 28 LBS



FIXTURE WEIGHT 38 LBS




FIXTURE WEIGHT 58 LBS




NS2-P1AH-26-GW-PAL/PBR




NS2-P1ED-26-GW-BAL



FIXTURE WEIGHT 28 LBS



FIXTURE WEIGHT 38 LBS



FIXTURE WEIGHT 58 LBS

MATCHING FIXTURES



page 356



page 388

FEATURES

- The Nimbus pendant is an adaptation of a theater fixture designed in the 1920s.
- A small acrylic dome or flat lens accents this deco-style metal trim ring.
- Spun from solid, non-ferrous 0.040" thick brass or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS
<p>NS1 (FLAT DIFFUSER)</p>	<p>P1AH PENDANT WITH 3 ANGLED STEMS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY</p>	26	<p>GW GLOSS WHITE ACRYLIC</p>	<p>PAL POLISHED ALUMINUM</p>	<p>26"</p>	120	30	<p>DMA ADVANCE® DIMMING BALLAST</p>
			<p>MW MATTE WHITE ACRYLIC</p>	<p>BAL BRUSHED ALUMINUM</p>	<p>80D26 8@26W QD (11094.0)</p> <p>4BX39 4@39W BX (11090.0)</p> <p>3IN150 3@150W IN (13752.0)</p>	277	347	<p>DML LUTRON® DIMMING BALLAST</p> <p>EMI INTEGRAL EMERGENCY</p>
<p>NS2 (DOME DIFFUSER)</p>	<p>P1ED PENDANT WITH 3 ANGLED AIRCRAFT CABLES TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY</p>	34		<p>PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>	<p>34"</p>	347	40	<p>FUS FUSED</p>
					<p>P1GB PENDANT WITH 3 BEADED CHAINS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY</p>			<p>8TT32 8@32W TT</p> <p>6BX40 6@40W BX</p> <p>6BX50 6@50W BX (13755.0)</p> <p>6BX55 6@55W BX</p> <p>8BX39 8@39W BX</p>
		45			<p>45"</p>	347	50	<p>ULD UL DAMP LABEL</p> <p>TRC TRIPLE CIRCUIT</p>
			<p>8TT42 8@42W TT</p> <p>9BX39 9@39W BX (11092.0)</p> <p>9BX40 9@40W BX</p> <p>9BX50 9@50W BX (13756.0)</p> <p>9BX55 9@55W BX</p> <p>8IN150 8@150W IN (13754.0)</p>					
<p>▾ SPECIFY CATALOG CODE</p>								


SAMPLE CODE: **NS2-P1ED-26-GW-BAL-4BX39-120-40-FUS**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM


- Fixture mounts to a standard 4" J-box (supplied by others), and features a 45-degree sloped-ceiling canopy.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.

- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For metal halide lamping contact factory.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.


NIMBUS™ PENDANT



FIXTURE WEIGHT 28 LBS



FIXTURE WEIGHT 38 LBS



FIXTURE WEIGHT 58 LBS



NS1-P16B-26-GW-BNP

MATCHING FIXTURES



page 356



page 388

FEATURES

- The Nimbus pendant is an adaptation of a theater fixture designed in the 1920s.
- A small acrylic dome or flat lens accents this deco-style metal trim ring.
- Spun from solid, non-ferrous 0.040" thick brass or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS
<p>NS1 (FLAT DIFFUSER)</p>	<p>P1AH PENDANT WITH 3 ANGLED STEMS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY</p>	26	<p>GW GLOSS WHITE ACRYLIC</p>	<p>PAL POLISHED ALUMINUM</p>	<p>26"</p>	120	27	<p>DMA ADVANCE® DIMMING BALLAST</p>
			<p>MW MATTE WHITE ACRYLIC</p>	<p>BAL BRUSHED ALUMINUM</p>	<p>80D26 8@26W QD (11094.0)</p> <p>4BX39 4@39W BX (11090.0)</p> <p>3IN150 3@150W IN (13752.0)</p>	277	347	<p>DML LUTRON® DIMMING BALLAST</p> <p>EMI INTEGRAL EMERGENCY</p>
<p>NS2 (DOME DIFFUSER)</p>	<p>P1ED PENDANT WITH 3 ANGLED AIRCRAFT CABLES TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY</p>	34		<p>PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>	<p>34"</p>		37	<p>FUS FUSED</p>
	<p>P1GB PENDANT WITH 3 BEADED CHAINS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY</p>	45			<p>45"</p>		48	<p>TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)</p> <p>ULD UL DAMP LABEL</p> <p>TRC TRIPLE CIRCUIT</p>
<p>↓ SPECIFY CATALOG CODE</p>								

SAMPLE CODE: **NS1-P1GB-26-GW-BNP-4BX39-120-40-FUS**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others), and features a 45-degree sloped-ceiling canopy.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.

- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For metal halide lamping contact factory.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.