


NS1-S1SA-12-GW-BNP

ADA



NS2-S1SA-12-GW-BAL

ADA

▾ MATCHING FIXTURES



page 194



page 388

▾ FEATURES

- The Nimbus sconce is an adaptation of a theater fixture designed in the 1920s.
- A small acrylic dome or flat lens accents this deco-style metal trim ring.
- Spun from solid, non-ferrous 0.040" thick brass or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size.
- Virgin white acrylic is UV stable and UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 <p>NS1 (FLAT DIFFUSER)</p> <p>NS2 (DOME DIFFUSER)</p>	<p>S1SA INDOOR ADA COMPLIANT SCNCE</p> 	<p>12</p>	<p>GW GLOSS WHITE ACRYLIC</p> <p>MW MATTE WHITE ACRYLIC</p>	<p>PAL POLISHED ALUMINUM</p> <p>BAL BRUSHED ALUMINUM</p> <p>PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>	<p>12" </p> <p>1QD13 1@13W QD</p> <p>2QD13 2@13W QD (13787.0)</p>	<p>120</p> <p>277</p> <p>347</p>	<p>EMR REMOTE MOUNT EMERGENCY</p> <p>FUS FUSED</p> <p>ULD UL DAMP LABEL</p>
<p>▾ SPECIFY CATALOG CODE</p>							

SAMPLE CODE: **NS2-S1SA-12-GW-BAL-2QD13-120-ULD**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Fixture is ADA compliant.
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.