



ODYSSEY™ PENDANT



OD1-P1EA-12-FR-SGP





OD1-P1EA-12-CL-SWP-PCL



FEATURES

- Simple, understated appearance makes the Odyssey well suited for a variety of commercial applications.
- Injection molded prismatic acrylic diffuser.
- Several interchangeable bottom diffuser options are available.
- Easy tool-less re-lamping.
- Suspended by a stainless steel aircraft cable.
- Fitter is spun from solid, non-ferrous 0.064" thick aluminum.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS
 <p>OD1</p>	<p>P1EA PENDANT WITH A SINGLE CENTER AIRCRAFT CABLE AND POWER CORD</p> 	12	CL CLEAR PRISMATIC ACRYLIC	PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	12"	120	34	DMA ADVANCE® DIMMING BALLAST REQUIRES 12" BALLAST CANOPY (SEE BELOW)
			FR FROSTED PRISMATIC ACRYLIC		20D26 2@26W QD	277		
			2TT32 2@32W TT (11629.0)		347			
			2TT42 2@42W TT					
			1IN150 1@150W IN (13750.0)					
		16	FG FROSTED GREEN PRISMATIC ACRYLIC		16"	40	DML LUTRON® DIMMING BALLAST REQUIRES 12" BALLAST CANOPY (SEE BELOW)	
			FB FROSTED BLUE PRISMATIC ACRYLIC		40D26 4@26W QD			
			4TT32 4@32W TT (13751.0)					
			4TT42 4@42W TT					
			1IN200 1@200W IN					
			NOTE: 16" NOT AVAILABLE IN COLORED ACRYLIC					
<p>▾ SPECIFY CATALOG CODE</p>								


PENDANT

SAMPLE CODE: OD1-P1EA-12-CL-SWP-2TT32-120-34-PCL

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Maximum overall height subject to ballast specification. Consult factory for details.

- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For metal halide lamping contact factory.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.



DMA/DML/EMI
REQUIRES 12" BALLAST CANOPY AND STEM