



FIXTURE WEIGHT 4 LBS



OR1-C1NA-12-GW-SGP

▾ MATCHING FIXTURES



page 354

▾ FEATURES

- The circular form of the Orb adapts well to numerous interior environments.
- Spun from solid, non-ferrous 0.064" thick aluminum.
- CNC-cut white acrylic diffuser is 1/4" thick.
- Tool-less access to lamp.
- Utilizes highly efficient, long lasting and low mercury T5 lamps for minimal fixture maintenance and lamp disposal.
- Virgin white acrylic is UV stable and UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 <p>OR1</p>	<p>C1NA SURFACE CEILING MOUNT </p>	<p>12</p>	<p>GW GLOSS WHITE ACRYLIC MW MATTE WHITE ACRYLIC</p>	<p>BAL BRUSHED ALUMINUM PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>	<p>12" 1CL22 1@22W T5 CIR</p>	<p>120 277 347</p>	<p>EMR REMOTE MOUNT EMERGENCY FUS FUSED ULD UL DAMP LABEL</p>
<p>↓ SPECIFY CATALOG CODE</p>							

SAMPLE CODE: **OR1-C1NA-12-GW-SGP-1CL22-120-EMR**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.