



OR1-S1SA-12-GW-BAL



LOCATION: RAC, St. Louis, MO

▾ MATCHING FIXTURES



page 442

▾ FEATURES

- The circular form of the Orb adapts well to numerous interior environments.
- Spun from solid, non-ferrous 0.064" thick aluminum.
- CNC-cut white acrylic diffuser is 1/4" thick.
- Virgin white acrylic is UV stable and UL-94 HB Flame Class rated.
- Tool-less access to lamp.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Utilizes highly efficient, long lasting and low mercury T5 lamps for minimal fixture maintenance and lamp disposal.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 <p>OR1</p>	<p>S1SA INDOOR ADA COMPLIANT SCNCE</p> 	<p>12</p>	<p>GW GLOSS WHITE ACRYLIC</p> <p>MW MATTE WHITE ACRYLIC</p>	<p>BAL BRUSHED ALUMINUM</p> <p>PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>	<p>12" </p> <p>1CL22 1@22W T5C (12882.0)</p>	<p>120</p> <p>277</p> <p>347</p>	<p>EMR REMOTE MOUNT EMERGENCY</p> <p>FUS FUSED</p> <p>ULD UL DAMP LABEL</p>
<p>☑ SPECIFY CATALOG CODE</p>							

SAMPLE CODE: **OR1-S1SA-12-GW-BAL-1CL22-120-FUS**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Fixture is ADA compliant.
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.