




ORION™ PENDANT




FIXTURE WEIGHT 25 LBS




FIXTURE WEIGHT 30 LBS



FIXTURE WEIGHT 35 LBS



FIXTURE WEIGHT 45 LBS




FIXTURE WEIGHT 65 LBS




ON1-P1AH-23-GW-PBR




ON1-P1ED-23-GW-BKP




FIXTURE WEIGHT 25 LBS




FIXTURE WEIGHT 30 LBS



FIXTURE WEIGHT 35 LBS



FIXTURE WEIGHT 45 LBS






FIXTURE WEIGHT 65 LBS



FEATURES

- The simple, shallow dome of the Orion is accented by tripod hanging systems.
- Available in diameters up to 72".
- Constructed with solid, non-ferrous brass or aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS		
 <p>ON1</p>	P1AH PENDANT WITH 3 ANGLED STEMS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY 	23	GW GLOSS WHITE ACRYLIC	PAL POLISHED ALUMINUM	23"	120	30	DMA ADVANCE® DIMMING BALLAST		
			MW MATTE WHITE ACRYLIC	BAL BRUSHED ALUMINUM	40D26 4@26W QD (10989.0)	277		DML LUTRON® DIMMING BALLAST		
		30	FA FAUX ALABASTER ACRYLIC	PBR POLISHED BRASS	3IN150 3@150W IN (13742.0)	347		36	EMI INTEGRAL EMERGENCY	
			NH NATURAL HORN ACRYLIC	BBR BRUSHED BRASS	30"	80D26 8@26W QD (12189.0)			FUS FUSED	
		36	P1ED PENDANT WITH 3 ANGLED AIRCRAFT CABLES TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY 	ET ETRUSCAN ACRYLIC	ABR ANTIQUE BRASS	4BX39 4@39W BX (9640.0)		42	48	TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)
				WS WHITE SWIRL ACRYLIC	STB STATUARY BRONZE	6BX39 6@39W BX (8668.0)				
	PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)			SNK SATIN NICKEL	6IN150 6@150W IN (13743.0)					
				ORB OIL RUBBED BRONZE	36"					
	42					8TT32 8@32W TT (13746.0)	54			
						6BX40 6@40W BX				
						6BX50 6@50W BX (13745.0)				
						6BX55 6@55W BX				
6IN150 6@150W IN (13743.0)										
42"										
60					9BX39 9@39W BX					
					9BX40 9@40W BX					
					9BX50 9@50W BX (13747.0)					
					9BX55 9@55W BX					
					8IN150 8@150W IN (13744.0)					
					60"					
					12BX39 12@39W BX					
					12BX40 12@40W BX					
					12BX50 12@50W BX (13748.0)					
					12BX55 12@55W BX					
					8IN150 8@150W IN (13744.0)					

↓ SPECIFY CATALOG CODE

SAMPLE CODE: ON1-P1ED-23-GW-BKP-4TT32-120-30-TLP

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others), and features a 45-degree sloped-ceiling canopy.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.

- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For metal halide lamping contact factory.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.