

PH1-C1NA-17-GW-BNP



PH1-C1NA-17-GW-BAL

MATCHING FIXTURES



page 218




page 222



page 368

FEATURES

- The sturdy trim ring of the Phoenix is accented by solid turned metal half-spheres.
- The Phoenix features a tapered cone-shaped diffuser and a stepped, bottom accent finial.
- Spun from solid, non-ferrous 0.040" thick brass or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 <p>PH1</p>	<p>C1NA SURFACE CEILING MOUNT</p> 	17	<p>GW GLOSS WHITE ACRYLIC</p>	<p>PAL POLISHED ALUMINUM</p>	<p>17"</p>	120	<p>DMA ADVANCE® DIMMING BALLAST</p>
		27	<p>MW MATTE WHITE ACRYLIC</p>	<p>BAL BRUSHED ALUMINUM</p>	<p>20D13 2@13W QD (13789.0)</p>	277	<p>DML LUTRON® DIMMING BALLAST</p>
				<p>PTR PEWTER</p>	<p>27"</p>	347	<p>EMR REMOTE MOUNT EMERGENCY (17" SIZE ONLY)</p>
				<p>PBR POLISHED BRASS</p>	<p>20D26 2@26W QD (13812.0)</p>		<p>EMI INTEGRAL EMERGENCY (27" SIZE ONLY)</p>
				<p>BBR BRUSHED BRASS</p>	<p>40D26 4@26W QD (12205.0)</p>		<p>FUS FUSED</p>
				<p>ABR ANTIQUE BRASS</p>			<p>ULD UL DAMP LABEL</p>
				<p>STB STATUARY BRONZE</p>			
				<p>SNK SATIN NICKEL</p>			
				<p>ORB OIL RUBBED BRONZE</p>			
				<p>PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>			

☐ SPECIFY CATALOG CODE

SAMPLE CODE: PH1-C1NA-17-GW-BAL-20D13-120-ULD

☒ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others) and may require additional anchors on larger sizes.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).

- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.