



PH1-S1SB-17-GW-BNP



PH1-S1SB-17-GW-AWP

▾ MATCHING FIXTURES



page 218



page 222



page 424

▾ FEATURES

- The sturdy trim ring of the Phoenix is accented by solid, turned metal half-spheres.
- The Phoenix features a tapered, cone-shaped diffuser and a stepped, bottom accent finial.
- Spun from solid, non-ferrous 0.040" thick brass or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 PH1	S1SB INDOOR SCNCE 	17	GW GLOSS WHITE ACRYLIC MW MATTE WHITE ACRYLIC	PAL POLISHED ALUMINUM BAL BRUSHED ALUMINUM PTR PEWTER PBR POLISHED BRASS BBR BRUSHED BRASS ABR ANTIQUE BRASS STB STATUARY BRONZE SNK SATIN NICKEL ORB OIL RUBBED BRONZE PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	17" 2QD13 2@13W QD 2IN60 2@60W IN 27" 2QD26 2@26W QD (12201.0) 2IN100 2@100W IN (13792.0)	120 277 347	DMA ADVANCE® DIMMING BALLAST DML LUTRON® DIMMING BALLAST EMR REMOTE MOUNT EMERGENCY FUS FUSED ULD UL DAMP LABEL TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)
		27					
<input type="button" value="SPECIFY CATALOG CODE"/>							

SAMPLE CODE: PH1-S1SB-17-GW-AWP-2QD13-120-ULD

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.