


FIXTURE WEIGHT 4 LBS



FIXTURE WEIGHT 5 LBS



PC1-S1SA-14-GW-PBR

ADA




PC1-S1SA-14-GW-PAL

ADA



FEATURES

- The Priscilla sconce features a luminous acrylic diffuser framed by a sleek metal trim ring constructed from solid non-ferrous brass or aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 <p>PC1</p>	<p>S1SA INDOOR ADA COMPLIANT SCNCE </p>	14	<p>GW GLOSS WHITE ACRYLIC</p>	<p>PAL POLISHED ALUMINUM</p>	<p>14" </p>	120	<p>DMA ADVANCE® DIMMING BALLAST</p>
		20	<p>MW MATTE WHITE ACRYLIC</p>	<p>BAL BRUSHED ALUMINUM</p>	<p>1QD26 1@26W QD (13781.0)</p>	277	<p>DML LUTRON® DIMMING BALLAST</p>
		<p>FA FAUX ALABASTER ACRYLIC</p>	<p>PTR PEWTER</p>	<p>2IN40 2@40W IN</p>	347	<p>EMR REMOTE MOUNT EMERGENCY</p>	
		<p>NH NATURAL HORN ACRYLIC</p>	<p>PBR POLISHED BRASS</p>	<p>20" </p>	<p>FUS FUSED</p>		
		<p>ET ETRUSCAN ACRYLIC</p>	<p>BBR BRUSHED BRASS</p>	<p>2QD26 2@26W QD</p>	<p>ULD UL DAMP LABEL</p>		
		<p>WS WHITE SWIRL ACRYLIC</p>	<p>ABR ANTIQUE BRASS</p>	<p>2IN40 2@40W IN (13808.0)</p>	<p>TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)</p>		
			<p>STB STATUARY BRONZE</p>				
			<p>SNK SATIN NICKEL</p>				
			<p>ORB OIL RUBBED BRONZE</p>				
			<p>PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>				

▾ SPECIFY CATALOG CODE

SAMPLE CODE: PC1-S1SA-14-GW-PAL-1QD26-120-TLP

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Fixture is ADA compliant.
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.

SCNCE