



PRISM™ PENDANT



FIXTURE WEIGHT 10 LBS



FIXTURE WEIGHT 20 LBS



PR1-P1AA-16-FB-SMP





PR1-P1AA-16-FR-BLP



FEATURES

- The Prism features laser-cut aluminum fins and bottom ring.
- Base fixture comes standard in silver metallic powder coat paint. Fins can be painted in an accent color.
- Injection molded prismatic acrylic diffuser.
- Unique bottom diffuser eliminates harsh glare from lamps while still transmitting light.
- Tool-less access to lamp through bottom opening.
- Canopy and fitter are spun from solid, non-ferrous 0.064" thick aluminum.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.


SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS
 <p>PR1</p>	<p>P1AA PENDANT WITH A SINGLE CENTER STEM</p> 	16	CL CLEAR PRISMATIC ACRYLIC	BAL BRUSHED ALUMINUM PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	16" 10D26 1@26W QD	120 277 347	34	DMA ADVANCE® DIMMING BALLAST REQUIRES 12" BALLAST CANOPY (SEE BELOW) DML LUTRON® DIMMING BALLAST REQUIRES 12" BALLAST CANOPY (SEE BELOW)
			FR FROSTED PRISMATIC ACRYLIC		1TT32 1@32W TT			
			FG FROSTED GREEN PRISMATIC ACRYLIC		1TT42 1@42W TT (12223.0)			
			FB FROSTED BLUE PRISMATIC ACRYLIC		1TT57 1@57W TT			
			1TT70 1@70W TT		1IN150 1@150W IN (13750.0)			
			19"		40			
		19	AM AMBER PRISMATIC ACRYLIC	4QD26 4@26W QD	40	EMI INTEGRAL EMERGENCY REQUIRES 12" BALLAST CANOPY (SEE BELOW) FUS FUSED ULD UL DAMP LABEL		
			RP RED PRISMATIC ACRYLIC	4TT32 4@32W TT (13751.0)				
			GR GREEN PRISMATIC ACRYLIC	4TT42 4@42W TT				
			2TT57 2@57W TT	2TT70 2@70W TT				
			1IN200 1@200W IN					
NOTE: 19" NOT AVAILABLE IN COLORED ACRYLIC								
<input type="button" value="SPECIFY CATALOG CODE"/>								

SAMPLE CODE: PR1-P1AA-16-FR-BLP-1TT32-120-34-FUS

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others), and features a 45-degree sloped-ceiling canopy.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Maximum overall height subject to ballast specification. Consult factory for details.

- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For metal halide lamping contact factory.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.



DMA/DML/EMI
REQUIRES 12" BALLAST CANOPY