



REFLECTION™ SCONCE



RF1-S1SC-16-GW-SGP/BAL

▼ MATCHING FIXTURES



page 180



page 184





page 316



page 426

▼ FEATURES

- The Reflection arm sconce features double-stacked trim rings and a shallow diffuser that rest on top of a sturdy arm assembly, creating a striking wall luminaire.
- Light spills between the two low-profile trim rings.
- The simple, understated look of this fixture is well suited for numerous interior applications.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size.
- Virgin white acrylic is UV stable and UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

| SERIES   | HANGING SYSTEM  | SIZE | DIFFUSER   | FINISH  | LAMPING (PHOTOMETRIC TEST #)   | VOLTAGE  | OPTIONS   |
|--|---|------|--|---|--|--|---|
| <br>RF1 | S1SC ARM SCONCE  | 16   | <b>GW</b> GLOSS WHITE ACRYLIC<br><br><b>MW</b> MATTE WHITE ACRYLIC | <b>PAL</b> POLISHED ALUMINUM<br><br><b>BAL</b> BRUSHED ALUMINUM<br><br><b>PTR</b> PEWTER<br><br><b>PBR</b> POLISHED BRASS<br><br><b>BBR</b> BRUSHED BRASS<br><br><b>ABR</b> ANTIQUE BRASS<br><br><b>STB</b> STATUARY BRONZE<br><br><b>SNK</b> SATIN NICKEL<br><br><b>ORB</b> OIL RUBBED BRONZE<br><br>PTD PAINTED - SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS) | <b>16"</b><br><br><b>2QD26</b> 2@26W QD (13771.0)<br><br><b>2IN100</b> 2@100W IN (7135.0)<br><br><b>26"</b><br><br><b>4QD26</b> 4@26W QD (10989.0)<br><br><b>4TT32</b> 4@32W TT (9529.0)<br><br><b>2BX39</b> 2@39W BX (13772.0)<br><br><b>3IN150</b> 3@150W IN (13742.0) | <b>120</b><br><br><b>277</b><br><br><b>347</b> | <b>DMA</b> ADVANCE® DIMMING BALLAST<br><br><b>DML</b> LUTRON® DIMMING BALLAST<br><br><b>EMI</b> INTEGRAL EMERGENCY<br><br><b>FUS</b> FUSED<br><br><b>ULD</b> UL DAMP LABEL<br><br><b>TLP</b> TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT) |
|  |   | 26   |  |   |  |  |   |
| SPECIFY CATALOG CODE   |   |      |  |   |  |  |   |

SAMPLE CODE: **RF1-S1SC-16-GW-SGP/BAL-2QD26-120-FUS**

PHOTOMETRIC INFORMATION AVAILABLE AT [WWW.OCL.COM](http://WWW.OCL.COM)

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.
- ADA compliant version available.
- For photometric data, please visit [www.ocl.com](http://www.ocl.com).
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.