




REFLECTION™ PENDANT




FIXTURE WEIGHT 22 LBS



FIXTURE WEIGHT 30 LBS



FIXTURE WEIGHT 45 LBS




FIXTURE WEIGHT 70 LBS




RF1-P1ED-26-GW-SGP/BAL




RF1-P1AE-26-GW-BAL




FIXTURE WEIGHT 22 LBS



FIXTURE WEIGHT 30 LBS



FIXTURE WEIGHT 45 LBS



FIXTURE WEIGHT 70 LBS

MATCHING FIXTURES



page 184



page 316





page 318



page 426

FEATURES

- The Reflection pendant features two elegant trim rings through which there is a soft glow of light.
- Spun from solid, non-ferrous 0.040" thick brass or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick depending on size.
- Virgin white acrylic is UV stable and UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS
 <p>RF1</p>	<b>P1AE</b> PENDANT WITH 4 VERTICAL STEMS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY 	16	<b>GW</b> GLOSS WHITE ACRYLIC	<b>PAL</b> POLISHED ALUMINUM	<b>16"</b>	<b>120</b>	21	<b>DMA</b> ADVANCE® DIMMING BALLAST
			<b>MW</b> MATTE WHITE ACRYLIC	<b>BAL</b> BRUSHED ALUMINUM	<b>20D26</b> 2@26W QD (13771.0)	<b>277</b>		<b>DML</b> LUTRON® DIMMING BALLAST
		26	<b>PTR</b> PEWTER	<b>21N100</b> 2@100W IN (7135.0)	<b>347</b>	<b>EMI</b> INTEGRAL EMERGENCY		
			<b>PBR</b> POLISHED BRASS	<b>26"</b>		32	<b>FUS</b> FUSED	
			<b>BBR</b> BRUSHED BRASS	<b>40D26</b> 4@26W QD (10989.0)			<b>TLP</b> TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)	
			<b>ABR</b> ANTIQUE BRASS	<b>4TT32</b> 4@32W TT (9529.0)		40	<b>CIB</b> CLEAR INNER BOWL	
	<b>STB</b> STATUARY BRONZE	<b>2BX39</b> 2@39W BX (13772.0)		<b>ULD</b> UL DAMP LABEL				
	33	<b>SNK</b> SATIN NICKEL	<b>31N150</b> 3@150W IN (13742.0)		50	<b>TRC</b> TRIPLE CIRCUIT		
		<b>ORB</b> OIL RUBBED BRONZE	<b>33"</b>			<b>DNL</b> PAR DOWN LIGHT		
		<b>PTD</b> PAINTED - SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	<b>80D26</b> 8@26W QD (12189.0)			<b>BFL</b> BOTTOM FINIAL (SEE BELOW)		
		<b>6BX39</b> 6@39W BX (8668.0)						
		<b>6BX40</b> 6@40W BX						
<b>6BX50</b> 6@50W BX								
41		<b>61N150</b> 6@150W IN (13743.0)						
		<b>41"</b>						
		<b>8TT42</b> 8@42W TT (13749.0)						
		<b>9BX39</b> 9@39W BX						
		<b>9BX40</b> 9@40W BX						
		<b>9BX50</b> 9@50W BX (13747.0)						
	<b>9BX55</b> 9@55W BX							
		<b>8IN150</b> 8@150W IN (13744.0)						

↓ SPECIFY CATALOG CODE

SAMPLE CODE: RF1-P1AE-26-GW-BAL-4TT32-120-40-CIB

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others), and features a 45-degree sloped-ceiling canopy.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.
- Bottom finial option increases overall height by length of the finial.

- For photometric data, please visit [www.ocl.com](http://www.ocl.com).
- For lamp and base information, see pages 496-505 in the reference section.
- Par down light option available in combination with a variety of compact fluorescent reflectors.
- For metal halide lamping contact factory.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.



**BFL**  
BOTTOM FINIAL