


SC1-S1SC-07-WG-PBR



CN1-S1SC-10-WG-BKP

▼ MATCHING FIXTURES



page 80



page 80







page 420



page 420

▼ FEATURES

- The Schoolhouse and Cone series feature unique styles of hand-blown, opal white glass with a minimum wall thickness of 0.150".
- This timeless fixture is available with energy efficient compact fluorescent lighting.
- Constructed from solid non-ferrous brass, aluminum or copper.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 <p>SC1</p>	<p>S15C ARM SCONCE</p> 	07	<p>WG WHITE GLASS</p>	<p>PAL POLISHED ALUMINUM BAL BRUSHED ALUMINUM PTR PEWTER PBR POLISHED BRASS BBR BRUSHED BRASS ABR ANTIQUE BRASS STB STATUARY BRONZE SNK SATIN NICKEL ORB OIL RUBBED BRONZE PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>	<p>7" 10D13 1@13W QD 1IN60 1@60W IN 10" 10D26 1@26W QD 1IN100 1@100W IN</p>	<p>120 277 347</p>	<p>EMR REMOTE MOUNT EMERGENCY FUS FUSED ULD UL DAMP LABEL</p>
		10					
 <p>CN1</p>	<p>S15C ARM SCONCE</p> 	10	<p>WG WHITE GLASS</p>	<p>PAL POLISHED ALUMINUM BAL BRUSHED ALUMINUM PTR PEWTER PBR POLISHED BRASS BBR BRUSHED BRASS ABR ANTIQUE BRASS STB STATUARY BRONZE SNK SATIN NICKEL ORB OIL RUBBED BRONZE PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>	<p>10" 10D26 1@26W QD 1IN100 1@100W IN</p>	<p>120 277 347</p>	<p>EMR REMOTE MOUNT EMERGENCY FUS FUSED ULD UL DAMP LABEL</p>
		10					
<p>▾ SPECIFY CATALOG CODE</p>							

SAMPLE CODE: CN1-S15C-10-WG-BKP-10D26-120-FUS

↑ PHOTOMETRIC INFORMATION AVAILABLE AT [WWW.OCL.COM](http://WWW.OCL.COM)

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- For photometric data, please visit [www.ocl.com](http://www.ocl.com).
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.